

INDUSTRIAL COMPONENT DATA

NBC-MSD/70,0-93B/MSD SCO 1418259 PHOENIX CONTACT

Network cable NBC-MSD/70,0-93B/MSD SCO 1418259

Brand: PHOENIX CONTACT | Manufacturer Part Number: NBC-MSD/70,0-93B/MSD SCO



Manufacturer	PHOENIX CONTACT
MPN / Reference	NBC-MSD/70,0-93B/MSD SCO
Catalog number	1418259
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-480C31B30D
Generated	2026-08-04

Product Overview

Network cable - NBC-MSD/70,0-93B/MSD SCO - 1418259

Network cable, PROFINET CAT5 (100 Mbps), EtherCAT® CAT5 (100 Mbps), 4-position, PVC/PVC, green RAL 6018, shielded (Advanced Shielding Technology), Plug straight M12, coding: D / IP67, on Plug straight M12, coding: D / IP67, cable length: 70 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Technical dataNotesGeneral This product corresponds to the PROFINET Cabling and Interconnection Technology Guideline for PROFINET regulations, version 2.00, order no: 2.252, Chapter 10.1 Cord Sets for Balanced Cabling

General Further products with variable cable type and variable cable length can be found in the accessories section

Product propertiesProduct type Data cable preassembled

Application Standard

Sensor type PROFINET

Number of positions 4

No. of cable outlets 1

Shielded yes

Coding D

Insulation characteristics

Overvoltage category II

Degree of pollution 3
InterfacesBus system PROFINET
Signal type/category PROFINET CAT5 (IEC 11801), 100 Mbps
EtherCAT® CAT5 (IEC 11801), 100 Mbps
SignalingStatus display no
Status display present No
Electrical propertiesNominal voltage UN 48 V AC
60 V DC
Nominal current IN 4 A
Transmission medium Copper
Transmission characteristics (category) CAT5 (IEC 11801:2002)
Material specificationsFlammability rating according to UL 94 V0
ConnectorConnection 1
Type Plug straight M12 / IP67
Number of positions 4
Coding type D (Data)
Handle color black
Material CuSn (Contact)
Ni/Au (Contact surface)
PA (Contact carriers)
TPU, hardly inflammable, self-extinguishing (Grip body)
Zinc die-cast, nickel-plated (Screw connection)
FKM (Seal)
Insertion/withdrawal cycles ≥ 100
Insulation resistance $\geq 100 \text{ M}\Omega$
Tightening torque 0.4 Nm
Degree of protection IP67
Ambient temperature (operation) -25 °C ... 90 °C
Connection 2
Type Plug straight M12 / IP67
Number of p...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / NBC-MSD/70,0-93B/MSD SCO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.