

INDUSTRIAL COMPONENT DATA

NBC-M12MSX/10,0-94C/R4AC 1418871 PHOENIX CONTACT

Network cable NBC-MSX/10,0-94C/R4AC SCO 1418871

Brand: PHOENIX CONTACT | Manufacturer Part Number: NBC-M12MSX/10,0-94C/R4AC



Manufacturer	PHOENIX CONTACT
MPN / Reference	NBC-M12MSX/10,0-94C/R4AC
Catalog number	1418871
Category	Sensor-actuator patch cord
Minimum order	25 Pcs
Document ID	EO-9B6D9E559A
Generated	2026-08-05

Product Overview

Network cable - NBC-MSX/10,0-94C/R4AC SCO - 1418871

Network cable, CAT5 Ethernet, 8-pole, PUR, water blue RAL 5021, shielded, M12 SPEEDCON / IP67 straight connector, cable length: 10 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Network cable, Ethernet CAT5, 8-position, PUR, water blue RAL 5021, shielded, Plug straight M12 SPEEDCON / IP67, cable length: 10 m

Key Commercial Data

Orderkey 1418871

Packing unit 1

GTIN 4055626155289

Custom tariff number 85444290

Dimensions

Length of cable 10 m

Ambient conditions

Ambient temperature (operation) -25 °C ... 90 °C (M12 connector)

-20 °C ... 70 °C (RJ45 connector)

General data

Rated current at 40°C 0.5 A
Rated voltage 48 V AC
60 V DC
Number of positions 8
Signal type/category Ethernet CAT5
Standards/regulations M12 connector IEC 61076-2-109
Contact material CuSn
Contact carrier material PP
Contact surface material Ni/Au
Housing material Plastic
Characteristics head 1
Head type Plug straight M12 SPEEDCON / IP67
No. of positions (pin connector pattern) 8
Color black
Material (component) CuZn (Contact)
Standards and Regulations
Standard designation M12 connector
Standards/regulations IEC 61076-2-109
Cable
Cable type Ethernet drag chain CAT5
Cable type (abbreviation) 94C
UL AWM style 20963 (80°C/30 V)
Signal type/category Ethernet CAT5 (IEC 11801), 1 Gbps
Cable structure 4x2xAWG26/19; S/UTP
Conductor cross section 4x 2x 0.14 mm²
AWG signal line 26
Conductor structure signal line 19x 0.10 mm
Core diameter including insulation 1 mm
Wire colors white/blue-blue, white/orange-orange, white/green-green, white/brown-brown
Twisted pairs 2 cores to the pair
Overall twist Four pairs and four fillers to the core
Shielding Tinned copper braided shield
Optical shield covering...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / NBC-M12MSX/10,0-94C/R4AC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.