

INDUSTRIAL COMPONENT DATA

NBC-MSY/4,1-94H/MSY NTES 1415742 PHOENIX CONTACT

Hybrid cable NBC-MSY/4,1-94H/MSY NTES 1415742

Brand: PHOENIX CONTACT | Manufacturer Part Number: NBC-MSY/4,1-94H/MSY NTES



Manufacturer	PHOENIX CONTACT
MPN / Reference	NBC-MSY/4,1-94H/MSY NTES
Catalog number	1415742
Category	Sensor-actuator patch cord
Minimum order	100 Pcs
Document ID	EO-5AFAC1014E
Generated	2026-08-05

Product Overview

Hybrid cable - NBC-MSY/4,1-94H/MSY NTES - 1415742

Hybrid cable, Ethernet hybrid CAT5 (100 Mbps), Ethernet hybrid CAT5 (100 Mbps), 8-position, PUR halogen-free, black RAL 9005, shielded, Plug straight M12 SPEEDCON, coding: Y / IP67, on Plug straight M12 SPEEDCON, coding: Y / IP67, cable length: 4.1 m, Power with Ethernet (PWE)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Technical dataProduct propertiesProduct type Data cable preassembled
 Application Network, hybrid cable
 Sensor type Ethernet hybrid
 Number of positions 8
 No. of cable outlets 1
 Shielded yes
 Coding Y
 InterfacesBus system Ethernet
 Signal type/category Ethernet hybrid CAT5 (IEC 11801:2002), 100 Mbps
 Ethernet hybrid CAT5 (TIA 568B:2001), 100 Mbps
 SignalingStatus display no
 Status display present No

Electrical propertiesNominal voltage UN 30 V AC (Power and data)

30 V DC

Nominal current IN 6 A (Power)

0.5 A (Data)

Transmission medium Copper

Transmission characteristics (category) CAT5 (IEC 11801:2002)

ConnectorConnection 1

Type Plug straight M12 SPEEDCON / IP67

Number of positions 8 (4+4)

Locking type SPEEDCON

Coding type Y (Hybrid)

Shielded yes

Handle color black

Material CuZn (Contact)

Ni/Au (Contact surface)

PP (Contact carrier, data)

PA (Contact carrier, power)

TPU, hardly inflammable, self-extinguishing (Grip body)

Zinc die-cast, nickel-plated (Screw connection)

Insertion/withdrawal cycles ≥ 100

Insulation resistance $\geq 100 \text{ M}\Omega$

Tightening torque 0.4 Nm

Degree of protection IP67

Ambient temperature (operation) -25 °C ... 90 °C

Connection 2

Type Plug straight M12 SPEEDCON / IP67

Number of positions 8 (4+4)

Locking type SPEEDCON

Coding type Y (Hybrid)

Shielded yes

Handle color black

Material CuZn (Contact)

Ni/Au (Contact surface)

PA (Contact carrier, data)

PA (Contact carrier, power)

TPU, hardly inflammable, self-extinguishing (Grip body)

Zinc die-cast, nickel-plated (Screw connec...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / NBC-MSY/4,1-94H/MSY NTES with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.