

INDUSTRIAL COMPONENT DATA

NBC-P12MSD/ 5,0-93E/P12FSD 1476058 PHOENIX CONTACT

Network cable, CAT5 Ethernet (100 MBit/s), 4-pole, haloge..

Brand: PHOENIX CONTACT | Manufacturer Part Number: NBC-P12MSD/ 5,0-93E/P12FSD



Manufacturer	PHOENIX CONTACT
MPN / Reference	NBC-P12MSD/ 5,0-93E/P12FSD
Catalog number	1476058
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-BD2DB244AC
Generated	2026-08-02

Product Overview

Network cable, CAT5 Ethernet (100 MBit/s), 4-pole, halogen-free PUR, water blue RAL 5021, shielded (Advanced Shielding Technology), Straight M12 Push-pull connector, encoding: D / IP67, to Straight female M12 Push-pull, encoding: D / IP67, cable length: 5 m

Network cable, Ethernet CAT5 (100 MBit/s), 4-pole, shielded (Advanced Shielding Technology), M12 straight connector, coding: D Push-pull / IP67, a Straight female M12, coding: D Push-pull / IP67, cable length: 5 m

Network cable, Ethernet CAT5 (100 MBit/s), 4-pole, shielded (Advanced Shielding Technology), M12 Push-pull straight connector, coding: D/IP67, a Straight female M12 Push-pull, coding: D/IP67, cable length: 5 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Technical dataItem PropertiesProduct Type Ready-made data cable

Sensor Type Ethernet

Number of poles 4

application Standard

Shielded Yes

InterfacesBus system Ethernet

Signal Type/Category Ethernet CAT5 (IEC 11801), 100 MBit/s

SignageStatus Indication No

Available Status Indication No

Electrical PropertiesNominal voltage UN 48 V AC
60 V DC
Nominal Current IN 1.5 A
Transmission Medium copper
Transmission Characteristics (Category) CAT5 (IEC 11801:2002)
ConnectorsConnection 1
Construction M12 Push-pull / IP67 Straight Connector
Number of poles 4
Locking system Push-pull
Encoding Type D (Data)
Grip body color black
Flammability class according to UL 94 V0
Material CuSn (Contact)
Ni/Au (Surface Contacts)
PA (Contact Support)
TPU, low flammable, self-extinguishing (Grip body)
Zinc die-casting, nickel-plated (Screw connection)
FKM (Board)
Plug Cycles ≥ 100
Contact resistance $\leq 5 \text{ m}\Omega$
Insulation resistance $\geq 100 \text{ M}\Omega$
Surge Category II
Degree of pollution 3
Protection Index IP67
Ambient Temperature (Service) $-25^\circ\text{C} \dots 85^\circ\text{C}$
Connection 2
Construction Straight Female M12 Push-pull / IP67
Number of poles 4
Locking system Push-pull
Encoding Type D (Data)
Grip body color black
Flammability class according to UL 94 V0
Material CuSn (Contact)
Ni/Au (Surface Contacts)
PA (Contact Support)
TPU, low flammable, self-extinguishing (Grip body)
Zinc die-casting, nickel-plated (Screw connection)
FKM (Board)
Plug Cycles ≥ 100
Contact resistance $\leq 5 \text{ m}\Omega$
Insulation resistance $\geq 100 \text{ M}\Omega$
Degree of pollution....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / NBC-P12MSD/ 5,0-93E/P12FSD with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.