

INDUSTRIAL COMPONENT DATA

NBC-P12MSD/ 5,0-93E/P12MSD 1476051 PHOENIX CONTACT

Network cable, CAT5 Ethernet (100 MBit/s), 4-pole, haloge..

Brand: PHOENIX CONTACT | Manufacturer Part Number: NBC-P12MSD/ 5,0-93E/P12MSD



Manufacturer	PHOENIX CONTACT
MPN / Reference	NBC-P12MSD/ 5,0-93E/P12MSD
Catalog number	1476051
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-2469934A7D
Generated	2026-08-02

Product Overview

Network cable, CAT5 Ethernet (100 MBit/s), 4-pole, halogen-free PUR, water blue RAL 5021, shielded (Advanced Shielding Technology), M12 Push-pull straight connector, encoding: D / IP67, a M12 Push-pull straight connector, encoding: D / IP67, cable length: 5 m

Network cable, CAT5 Ethernet (100 MBit/s), 4-pole, shielded (Advanced Shielding Technology), M12 straight connector, coding: D Push-pull / IP67, a M12 straight connector, coding: D Push-pull / IP67, cable length: 5 m

Network cable, Ethernet CAT5 (100 Mbit/s), 4-pole, shielded (Advanced Shielding Technology), M12 Push-Pull straight male connector, keying: D/IP67, over M12 Push-Pull straight male connector, keying: D/IP67, cable length: 5 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Technical characteristicsProduct PropertiesProduct Type Pre-assembled data cable

Sensor Type Ethernet

Number of poles 4

Application Standard

Armored Yes

InterfacesBus system Ethernet

Signal Type/Category CAT5 Ethernet (IEC 11801), 100 Mbps

SignageStatus display No

Presence of a status display No

Electrical properties Rated voltage UN 48 V AC
60 V DC
Rated Current IN 1.5 A
Transmission support Copper
Transmission properties (category) CAT5 (IEC 11801:2002)
Connector Connection 1
Type M12 Push-Pull Straight Male Connector / IP67
Number of poles 4
Lock Mode Push-Pull
Coding Type D (Data)
Colour Socket Surface black
Flammability class according to UL 94 V0
Material CuSn (Contact)
Ni/Au (Contact Surface)
PA (Contact Holder)
TPU, Flame Retardant, Self-Extinguishing (Plug Surface)
Zinc die-casting, nickel-plated (Screw connection)
FKM (Joint)
Plugging cycles ≥ 100
Contact resistance $\leq 5 \text{ m}\Omega$
Insulation resistance $\geq 100 \text{ M}\Omega$
Surge Category II
Degree of pollution 3
Ingress protection IP67
Ambient Temperature (Operating) $-25^\circ\text{C} \dots 85^\circ\text{C}$
Connection 2
Type M12 Push-Pull Straight Male Connector / IP67
Number of poles 4
Lock Mode Push-Pull
Coding Type D (Data)
Colour Socket Surface black
Flammability class according to UL 94 V0
Material CuSn (Contact)
Ni/Au (Contact Surface)
PA (Contact Holder)
TPU, Flame Retardant, Self-Extinguishing (Plug Surface)
Zinc die-casting, nickel-plated (Screw connection)
FKM (Joint)
Plugging cycles ≥ 100
Contact resistance $\leq 5 \text{ m}\Omega$
Insulation resistance $\geq 100 \text{ M}\Omega$

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / NBC-P12MSD/ 5,0-93E/P12MSD with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.