

INDUSTRIAL COMPONENT DATA

NBC-R4AC/0,2-93K/R4AC 1412097 PHOENIX CONTACT Patch cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: NBC-R4AC/0,2-93K/R4AC



Manufacturer	PHOENIX CONTACT
MPN / Reference	NBC-R4AC/0,2-93K/R4AC
Catalog number	1412097
Category	Patch cord copper (twisted pair)
Minimum order	50 Pcs
Document ID	EO-49B8C1B40B
Generated	2026-08-03

Product Overview

Patch cable

Sercos III patch cable, shielded, star quadrant, flexible AWG 22 (7 wires), RAL 3020 (traffic red), RJ45/IP20 male connector, straight, to RJ45/IP20 male, straight, length: 0.3 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data

Orderkey 1412097

Packing unit 1 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

GTIN 4046356949491

Weight per Piece (excluding packing) 37.600 g

Custom tariff number 85444210

Country of origin PL (Poland)

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 5.119030300eCl@ss 6.027061800eCl@ss 7.027060308eCl@ss 8.027060308eCl@ss 9.027060308

ETIM 4.0EC002498ETIM 5.0EC002599

UNSPSC 13.226121604

ETIM for 1412097 Sensors (EC001855)

Feature Name

Feature Value

Number of poles (EF001391)

4

Type of electrical connection, field-sided (EF005525)

Other

Type of plug-in contact, field sided (EF006269)

Male (plug)

Positioning cable feed, field-sided (EF005928)

Straight

Type of electrical connection, box-sided (EF005524)

Other

Type of plug-in contact, box-sided (EF008386)

Male (plug)

Positioning cable feed, box-sided (EF005927)

Straight

Cable length (EF000536)

0.2 m

Material of cable sheath (EF004136)

Polyvinyl chloride (PVC)

Halogen free (EF000025)

No

Colour cable sheath (EF008249)

Other

With LED indication (EF005950)

No

Screened (EF000881)

Yes

Vulcanize (EF004115)

No

Material contact body (EF008248)

Other

Permitted cable outer temperature after assembling without vibration (EF001686)

-40 °C

Permitted cable outer temperature during assembling/handling (EF001685)

-40 °C

Degree of protection (IP) (EF005474)

Other

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / NBC-R4AC/0,2-93K/R4AC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.