

**INDUSTRIAL COMPONENT DATA**

# NBC-R4ACS/0,3-93C/R4ACS 1112940 PHOENIX CONTACT

## Patch cable, RJ45/IP20 straight to RJ45/IP20 straight, cable..

Brand: PHOENIX CONTACT | Manufacturer Part Number: NBC-R4ACS/0,3-93C/R4ACS



|                 |                            |
|-----------------|----------------------------|
| Manufacturer    | PHOENIX CONTACT            |
| MPN / Reference | NBC-R4ACS/0,3-93C/R4ACS    |
| Catalog number  | 1112940                    |
| Category        | Sensor-actuator patch cord |
| Minimum order   | 1 Pcs                      |
| Document ID     | EO-2AB3F4A0B4              |
| Generated       | 2026-08-04                 |

### Product Overview

Patch cable, RJ45/IP20 straight to RJ45/IP20 straight, cable length: 0.3 m, number of poles: 4, 100 MBit/s, CAT5, PROFINET, 1x4xAWG22/7, SF/TQ, green RAL 6018  
Patch cable, protection rating: IP20, cable length: 0.3 m, 100 MBit/s, CAT5, cable output: straight

**STRUCTURED PRODUCT DATA**

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Field Device Connectors (FDC)**

### Additional Product Information

ETIM for 1112940 Sensors (EC001855)  
Feature Name  
Feature Value  
Number of poles (EF001391)  
4  
Type of electrical connection, field-sided (EF005525)  
Other  
Type of plug-in contact, field sided (EF006269)  
Male (plug)  
Positioning cable feed, field-sided (EF005928)  
Straight  
Type of electrical connection, box-sided (EF005524)  
Other

Type of plug-in contact, box-sided (EF008386)  
Male (plug)  
Positioning cable feed, box-sided (EF005927)  
Straight  
Cable length (EF000536)  
0.3 m  
Material of cable sheath (EF004136)  
Other  
Halogen free (EF000025)  
No  
Colour cable sheath (EF008249)  
Other  
With LED indication (EF005950)  
No  
Screened (EF000881)  
Yes  
Vulcanize (EF004115)  
No  
Material contact body (EF008248)  
Other  
Material of contact surface (EF004020)  
Other  
Permitted cable outer temperature after assembling without vibration (EF001686)  
-40 °C  
Permitted cable outer temperature during assembling/handling (EF001685)  
-40 °C  
Degree of protection (IP) (EF005474)  
Other

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / NBC-R4ACS/0,3-93C/R4ACS with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.