

INDUSTRIAL COMPONENT DATA

NBC-R4ACS/1,0-93B/R4ACS 1112817 PHOENIX CONTACT

Patch cable, protection rating: IP20, cable length: 1 m, num..

Brand: PHOENIX CONTACT | Manufacturer Part Number: NBC-R4ACS/1,0-93B/R4ACS



Manufacturer	PHOENIX CONTACT
MPN / Reference	NBC-R4ACS/1,0-93B/R4ACS
Catalog number	1112817
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-1AE3DBCDF2
Generated	2026-08-04

Product Overview

Patch cable, protection rating: IP20, cable length: 1 m, number of poles: 4, 100 MBit/s, CAT5, material: PP, connection type: Pierce connection, cable output: straight, PROFINET

Patch cable, protection index: IP20, cable length: 1 m, 100 MBit/s, CAT5, cable output: straight

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

ETIM for 1112817 Sensors (EC001855)

Feature Name

Feature Value

Number of poles (EF001391)

4

Type of electrical connection, field-sided (EF005525)

Other

Type of plug-in contact, field sided (EF006269)

Male (plug)

Positioning cable feed, field-sided (EF005928)

Straight

Type of electrical connection, box-sided (EF005524)

Other

Type of plug-in contact, box-sided (EF008386)
Male (plug)
Positioning cable feed, box-sided (EF005927)
Straight
Cable length (EF000536)
1 m
Material of cable sheath (EF004136)
Polyvinyl chloride (PVC)
Halogen free (EF000025)
No
Colour cable sheath (EF008249)
Other
With LED indication (EF005950)
No
Screened (EF000881)
Yes
Vulcanize (EF004115)
No
Material contact body (EF008248)
Other
Material of contact surface (EF004020)
Other
Permitted cable outer temperature after assembling without vibration (EF001686)
-40 °C
Permitted cable outer temperature during assembling/handling (EF001685)
-40 °C
Degree of protection (IP) (EF005474)
Other

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / NBC-R4ACS/1,0-93B/R4ACS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.