

**INDUSTRIAL COMPONENT DATA**

# NBC-R4ACS/1,0-94C/OE 1113212 PHOENIX CONTACT Patch cable, protection index: IP20, cable length: 1 m, number ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: NBC-R4ACS/1,0-94C/OE



|                 |                            |
|-----------------|----------------------------|
| Manufacturer    | PHOENIX CONTACT            |
| MPN / Reference | NBC-R4ACS/1,0-94C/OE       |
| Catalog number  | 1113212                    |
| Category        | Sensor-actuator patch cord |
| Minimum order   | 1 Pcs                      |
| Document ID     | EO-2C2CE2AEC3              |
| Generated       | 2026-08-04                 |

## Product Overview

Patch cable, protection index: IP20, cable length: 1 m, number of poles: 8, 1 GBit/s, CAT5, material: PP, connection type: Pierce connection, connection section: AWG 26- 26, cable output: straight, Ethernet

Patch cable, protection rating: IP20, cable length: 1 m, 1 GBit/s, CAT5, connection section: AWG 26- 26, cable output: straight

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path      PHOENIX CONTACT &gt; Field Device Connectors (FDC)

## Additional Product Information

ETIM for 1113212 Sensors (EC001855)

Feature Name

Feature Value

Number of poles (EF001391)

8

Type of electrical connection, field-sided (EF005525)

Other

Positioning cable feed, field-sided (EF005928)

Other

Type of electrical connection, box-sided (EF005524)

Other

Type of plug-in contact, box-sided (EF008386)

Male (plug)  
Positioning cable feed, box-sided (EF005927)  
Straight  
Cable length (EF000536)  
1 m  
Material of cable sheath (EF004136)  
Other  
Halogen free (EF000025)  
No  
Colour cable sheath (EF008249)  
Other  
With LED indication (EF005950)  
No  
Screened (EF000881)  
Yes  
Vulcanize (EF004115)  
No  
Material contact body (EF008248)  
Other  
Material of contact surface (EF004020)  
Other  
Permitted cable outer temperature after assembling without vibration (EF001686)  
-40 °C  
Permitted cable outer temperature during assembling/handling (EF001685)  
-20 °C  
Degree of protection (IP) (EF005474)  
Other

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / NBC-R4ACS/1,0-94C/OE with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.