

INDUSTRIAL COMPONENT DATA

NBC-R4ACS/35,0-94F/R4ACS 1586506 PHOENIX CONTACT

Patch cable, protection index: IP20, cable length: 35 m, nu..

Brand: PHOENIX CONTACT | Manufacturer Part Number: NBC-R4ACS/35,0-94F/R4ACS



Manufacturer	PHOENIX CONTACT
MPN / Reference	NBC-R4ACS/35,0-94F/R4ACS
Catalog number	1586506
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-B71FED1994
Generated	2026-08-05

Product Overview

Patch cable, protection index: IP20, cable length: 35 m, number of poles: 8, 10 GBit/s, CAT6A, material: PP, connection type: Pierce connection, connection section: AWG 26- 26, cable output: straight, Ethernet

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)
--------------	---

Additional Product Information

ETIM for 1586506 Sensors (EC001855)

Feature Name

Feature Value

Number of poles (EF001391)

8

Type of electrical connection, field-sided (EF005525)

Other

Type of plug-in contact, field sided (EF006269)

Male (plug)

Positioning cable feed, field-sided (EF005928)

Straight

Type of electrical connection, box-sided (EF005524)

Other

Type of plug-in contact, box-sided (EF008386)

Male (plug)
Positioning cable feed, box-sided (EF005927)
Straight
Cable length (EF000536)
35 m
Material of cable sheath (EF004136)
Other
Halogen free (EF000025)
No
Colour cable sheath (EF008249)
Other
With LED indication (EF005950)
No
Screened (EF000881)
Yes
Vulcanize (EF004115)
No
Material contact body (EF008248)
Other
Material of contact surface (EF004020)
Other
Permitted cable outer temperature after assembling without vibration (EF001686)
-40 °C
Permitted cable outer temperature during assembling/handling (EF001685)
-20 °C
Degree of protection (IP) (EF005474)
Other

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / NBC-R4ACS/35,0-94F/R4ACS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.