

INDUSTRIAL COMPONENT DATA

NBC-R4ACS/50,0-93B/R4ACS 1441525 PHOENIX CONTACT

Patch cable, protection index: IP20, cable length: 50 m, nu..

Brand: PHOENIX CONTACT | Manufacturer Part Number: NBC-R4ACS/50,0-93B/R4ACS



Manufacturer	PHOENIX CONTACT
MPN / Reference	NBC-R4ACS/50,0-93B/R4ACS
Catalog number	1441525
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-7FBB4D5680
Generated	2026-08-01

Product Overview

Patch cable, protection index: IP20, cable length: 50 m, number of poles: 4, 100 MBit/s, CAT5, material: PP, connection type: Pierce connection, cable output: straight, PROFINET
Patch cable

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Field Device Connectors (FDC)**

Additional Product Information

ETIM for 1441525 Sensors (EC001855)
Feature Name
Feature Value
Number of poles (EF001391)
4
Type of electrical connection, field-sided (EF005525)
Other
Type of plug-in contact, field sided (EF006269)
Male (plug)
Positioning cable feed, field-sided (EF005928)
Straight
Type of electrical connection, box-sided (EF005524)
Other

Type of plug-in contact, box-sided (EF008386)
Male (plug)
Positioning cable feed, box-sided (EF005927)
Straight
Cable length (EF000536)
50 m
Material of cable sheath (EF004136)
Polyvinyl chloride (PVC)
Halogen free (EF000025)
No
Colour cable sheath (EF008249)
Other
With LED indication (EF005950)
No
Screened (EF000881)
Yes
Vulcanize (EF004115)
No
Material contact body (EF008248)
Other
Material of contact surface (EF004020)
Other
Permitted cable outer temperature after assembling without vibration (EF001686)
-40 °C
Permitted cable outer temperature during assembling/handling (EF001685)
-40 °C
Degree of protection (IP) (EF005474)
Other

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / NBC-R4ACS/50,0-93B/R4ACS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.