

INDUSTRIAL COMPONENT DATA

NBC- 5,0-93E/M12FSD 1407382 PHOENIX CONTACT Network cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: NBC-5,0-93E/M12FSD



Manufacturer	PHOENIX CONTACT
MPN / Reference	NBC-5,0-93E/M12FSD
Catalog number	1407382
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-6462B6643E
Generated	2026-08-05

Product Overview

Network cable

Network cable, CAT5 Ethernet (100 MBit/s), 4-pole, shielded, free cable end, to Straight female M12, encoding: D SPEEDCON / IP67, cable length: 5 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Key Commercial Data

Orderkey 1407382

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 403 (C-2-2017)

GTIN 4046356775106

Weight per Piece (excluding packing) 244.000 g

Custom tariff number 85444210

Country of origin PL (Poland)

Dimensions

Length of cable 5 m

Ambient conditions

Degree of protection IP65

IP67

Ambient temperature (operation) -25 °C ... 85 °C (M12 connector)

General data

Note Further products with variable cable type and variable cable length can be found in the accessories section

Rated current at 40°C 4 A (Plug/socket in accordance with IEC 61076-2-101, cable technical data is to be observed)

Rated voltage 48 V AC

60 V DC

Number of positions 4

Signal type/category Ethernet CAT5 (IEC 11801), 100 Mbps

Standards/regulations M12 connector IEC 61076-2-101

Contact material CuSn

Contact carrier material TPU GF

Contact surface material Ni/Au

Characteristics head 1

Head type free cable end

Characteristics head 2

Head type Socket straight M12 SPEEDCON / IP67

No. of positions (pin connector pattern) 4

Coding D (Data)

Color black

black

Material (component) CuZn (Contact)

Ni/Au (Contact surface)

TPU GF (Contact carriers)

TPU, hardly inflammable, self-extinguishing (Grip)

Zinc die-cast, nickel-plated (Screw connection)

Insulation resistance $\geq 100 \text{ M}\Omega$

Insertion/withdrawal cycles ≥ 100

Torque 0.4 Nm

Ambient temperature (operation) -25 °C ... 90 °C

Standards and Regulations

Standard designation M12 connector

Standards/regulations IEC 61076-2-101

Cable

Cabl...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / NBC-5,0-93E/M12FSD with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.