

INDUSTRIAL COMPONENT DATA

NBC-M12MSX/ 5,0-94F/R4AC 1407473 PHOENIX CONTACT

Network cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: NBC-M12MSX/ 5,0-94F/R4AC



Manufacturer	PHOENIX CONTACT
MPN / Reference	NBC-M12MSX/ 5,0-94F/R4AC
Catalog number	1407473
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-D5756B60B3
Generated	2026-08-05

Product Overview

Network cable

Network cable, Ethernet CAT6A (10 GBit/s), CC-Link IE CAT6A (10 GBit/s), 8-pole halogen-free, shielded (Advanced Shielding Technology), M12 straight connector, encoding: X / IP67, a RJ45 straight connector, encoding: X / IP20, cable length: 5 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Key Commercial Data

Orderkey 1407473

Packing unit 1 pc

Catalog page Page 407 (C-2-2017)

GTIN 4046356776714

Weight per Piece (excluding packing) 243.800 g

Custom tariff number 85444290

Country of origin PL (Poland)

Dimensions

Length of cable 5 m

Ambient conditions

Degree of protection IP65 (M12 connector)

IP67 (M12 connector)

IP20 (RJ45 connector)

Ambient temperature (operation) -25 °C ... 90 °C (M12 connector)

-20 °C ... 70 °C (RJ45 connector)

General data

Note Further products with variable cable type and variable cable length can be found in the accessories section

Rated current at 40°C 0.5 A

Rated voltage 48 V AC

60 V DC

Number of positions 8

Signal type/category Ethernet CAT6A, 10 Gbps

CC-Link IE CAT6A, 10 Gbps

Standards/regulations M12 connector IEC 61076-2-109

Contact material CuSn

Contact carrier material PP

Contact surface material Ni/Au

Housing material Plastic

Characteristics head 1

Head type Plug straight M12 SPEEDCON / IP67

No. of positions (pin connector pattern) 8

Coding X (Data)

Color black

Material (component) CuZn (Contact)

Ni/Au (Contact surface)

PP (Contact carriers)

TPU, hardly inflammable, self-extinguishing (Grip)

Zinc die-cast, nickel-plated (Screw connection)

Insulation resistance $\geq 100 \text{ M}\Omega$

Insertion/withdrawal cycles ≥ 100

Torque 0.4 Nm

Ambient temperature (operation) -25 °C ... 90 °C

Characteristics head 2

Head type Plug straight RJ45 / IP20

No. of positions (pin connector pattern) 8 (8)

Color gray

gray / black

Material (component) CuSn (Contact)

Ni/...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / NBC-M12MSX/ 5,0-94F/R4AC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.