


INDUSTRIAL COMPONENT DATA

NBC-M12MSX/ 2,0-94F 1407468 PHOENIX CONTACT Network cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: NBC-M12MSX/ 2,0-94F



Manufacturer	PHOENIX CONTACT
MPN / Reference	NBC-M12MSX/ 2,0-94F
Catalog number	1407468
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-A9292226D7
Generated	2026-08-03

Product Overview

Network cable

Network cable, Ethernet CAT6A (10 GBit/s), CC-Link IE CAT6A (10 GBit/s), 8-pole halogen-free, shielded (Advanced Shielding Technology), Straight M12 connector, encoding: X / IP67, a free cable end, encoding: X, cable length: 2 m

Network cable, Ethernet CAT6A (10 Gbps), CC-Link IE CAT6A (10 Gbps), 8-position, PUR halogen-free, water blue RAL 5021, shielded (Advanced Shielding Technology), Plug straight M12, coding: X / IP67, on free cable end, cable length: 2 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Technical dataNotesGeneral Further products with variable cable type and variable cable length can be found in the accessories section

Product propertiesProduct type Data cable preassembled

Application Standard

Sensor type Ethernet

Number of positions 8

No. of cable outlets 1

Shielded yes

Coding X

Data management status

Article revision 09

InterfacesBus system Ethernet
Signal type/category Ethernet CAT6A, 10 Gbps
CC-Link IE CAT6A, 10 Gbps
SignalingStatus display no
Status display present No
Electrical propertiesNominal voltage UN 48 V AC
60 V DC
Nominal current IN 0.5 A
Transmission medium Copper
Transmission characteristics (category) CAT6A
ConnectorConnection 1
Dimensional drawing Pin assignment of M12 plug, 8-pos., X-coded, pin side view
Type M12 Plug, straight, 8-position, shielded (Advanced Shielding Technology), Keying: X
Number of positions 8
Shielded yes
Shielding Advanced Shielding Technology
Signal type/category Ethernet CAT6A, 10 Gbps
CC-Link IE CAT6A, 10 Gbps
Insertion/withdrawal cycles ≥ 100
Insulation resistance $\geq 100 \text{ ?}$
Overvoltage category II
Degree of pollution 3
Tightening torque 0.4 Nm (M12 connector)
Material Contact CuZn
Material Contact surface Ni/Au
Material Contact carrier PA 6.6
Material Screw connection Die-cast zinc, nickel-plated
Material Grip body TPU, hardly inflammable, self-extinguishing
Material Seal FKM
Flammability rating according to UL 94 V0
Degree of protection IP65
IP67
Ambient temperature (operation) -25 °C ... 85 °C
Standard designatio...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / NBC-M12MSX/ 2,0-94F with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.