

INDUSTRIAL COMPONENT DATA

NFC 482S 1050841 PHOENIX CONTACT PLCnext Control with 4x 10/100/1000 Ethernet, controller PROFINET with safe..

Brand: PHOENIX CONTACT | Manufacturer Part Number: NFC 482S



Manufacturer	PHOENIX CONTACT
MPN / Reference	NFC 482S
Catalog number	1050841
Category	PLC CPU-module
Minimum order	1 Pcs
Document ID	EO-6739C15337
Generated	2026-08-02

Product Overview

PLCnext Control with 4x 10/100/1000 Ethernet, controller PROFINET with safety control system PROFIsafe integrated device PROFINET, protection index IP20, memory configuration plug-in
 PLCnext Control with 4x 10/100/1000 Ethernet, PROFINET controller with integrated PROFIsafe safety control system, PROFINET device, IP20 rating, pluggable parameterization memory

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Control Systems (CST)**

Additional Product Information

Data commercial
 Key order One million fifty thousand eight hundred forty one
 Packing unit 1 pcs
 Key selling DRAABC -
 EAN Four trillion fifty five billion six hundred twenty six million six hundred sixty nine thousand two hundred seventy four
 Unit weight (excluding packaging) 3.250,000 g
 Observation
 Environmental conditions
 Data Interfaces
 Power
 Standards and specifications
 Ratings

Dimensions

Mechanical construction

Time system using IEC 61131

General data

Environmental Product Compliance

Observation

Restriction of use EMC: class A product, see manufacturer's declaration in the download center

[Back to top](#)Dimensions

Width 122 mm

Height 182 mm

Depth 173 mm

[Back to top](#)Environmental conditions

Index of protection IP20

Room temperature (service) 0 °C ... 60 °C up to 2000 m above sea level (from 40 °C only with module ventilation)

0 °C ... 55 °C up to 3000 m above sea level (from 40 °C only with module ventilation)

Ambient temperature (storage / transport) -25 °C ... 70 °C

Humidity of air permissible (service) 10 % ... 95 % (without condensation)

Humidity of air permissible (storage / transport) 5 % ... 95 % (without condensation)

Air pressure (service) 80 kPa ... 108 kPa (up to 3000 m above NN)

Air pressure (storage / transport) 58 hPa ... 108 kPa (up to 4500 m above sea level)

[Back to top](#)Mechanical construction

Format 122 x 182 x 173 mm (W x h x d without module fan)

122 x 220 x 173 mm (W x h x d with integrated cooling fan)

Weight 2850 g

Observation about the indications of weig...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / NFC 482S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.