

INDUSTRIAL COMPONENT DATA

NS 15 PERF 500MM 1207645 PHOENIX CONTACT DIN rail perforated

Brand: PHOENIX CONTACT | Manufacturer Part Number: NS 15 PERF 500MM



Manufacturer	PHOENIX CONTACT
MPN / Reference	NS 15 PERF 500MM
Catalog number	1207645
Category	Mounting rail
Minimum order	20 Pcs
Document ID	EO-735CD2776E
Generated	2026-08-05

Product Overview

DIN rail perforated

Symmetrical perforated rail, according to EN 60715, material: Steel, galvanized, thick layer passivated, Standard profile, color: silver

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Enclosures connectivity

Additional Product Information

Key Commercial Data

Orderkey 1207645

Packing unit 20 pc

Minimum order quantity 20 pc

Note Made to Order (non-returnable)

GTIN 4046356366038

Weight per Piece (excluding packing) 999.000 g

Custom tariff number 72166190

Country of origin DE (Germany)

Dimensions

Height 5.5 mm

Length 500 mm

Width 15 mm

Hole width 12.20 mm

Hole height 4.20 mm

Drill hole spacing 20.00 mm

General

Material Steel

Coating galvanized, passivated with a thick layer

Color silver

Standards and Regulations

Test standard acc. to EN 60715

Connection in acc. with standard IEC / EN

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 4.023150301eCl@ss 4.123150301eCl@ss 5.027141143eCl@ss 5.127141100eCl@ss 6.027400600eCl@ss
7.027400602eCl@ss 8.027400602eCl@ss 9.027400602

ETIM 2.0EC001285ETIM 3.0EC001285ETIM 4.0EC000212ETIM 5.0EC000212ETIM 6.0EC001285

UNSPSC 6.0130212109UNSPSC 7.090139121708UNSPSC 1139121708UNSPSC 12.0139121708UNSPSC
13.239121708

ETIM for 1207645 Power distribution systems (EC001285)

Feature Name

Feature Value

Material (EF002169)

Steel

Surface protection (EF000139)

Other

Punch shape (EF001457)

Long-slot

Drill hole distance centrically (EF002677)

20 mm

Material thickness (EF000386)

1 mm

Length (EF001438)

500 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / NS 15 PERF 500MM with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.