

INDUSTRIAL COMPONENT DATA

NS 35/15 BLK UNPERF 410MM 4X5 5406268 PHOENIX CONTACT DIN rail, unperforated, width: 35 mm, height: 15 mm, a..

Brand: PHOENIX CONTACT | Manufacturer Part Number: NS 35/15 BLK UNPERF 410MM 4X5



Manufacturer	PHOENIX CONTACT
MPN / Reference	NS 35/15 BLK UNPERF 410MM 4X5
Catalog number	5406268
Category	Mounting rail
Minimum order	1 Pcs
Document ID	EO-E5C517B9F5
Generated	2026-08-04

Product Overview

DIN rail, unperforated, width: 35 mm, height: 15 mm, acc. to EN 60715, material: Steel, galvanized, length: 410 mm
Symmetrical rail without drilling, width: 35 mm, height: 15 mm, according to EN 60715, material: Steel, galvanized, length: 410 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Enclosures connectivity**

Additional Product Information

DIN rail, unperforated, width: 35 mm, height: 15 mm, acc. to EN 60715, material: Steel, galvanized, length: 410 mm

Key Commercial Data

Orderkey 5406268

Packing unit 1

GTIN 4055626012933

Custom tariff number 72166190

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCI@ss

eCl@ss 5.1 27141100
eCl@ss 6.0 27141100
eCl@ss 7.0 27141143
eCl@ss 8.0 27141143
eCl@ss 9.0 27400602
ETIM
ETIM 5.0 EC001285
ETIM 6.0 EC001285
ETIM 7.0 EC001285
UNSPSC
UNSPSC 13.2 39121708

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / NS 35/15 BLK UNPERF 410MM 4X5 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.