

**INDUSTRIAL COMPONENT DATA**

# NS 35/ 7,5 PERF 2M NZ REF CUT 1210239 PHOENIX CONTACT DIN rail perforated

Brand: PHOENIX CONTACT | Manufacturer Part Number: NS 35/ 7,5 PERF 2M NZ REF CUT



|                 |                               |
|-----------------|-------------------------------|
| Manufacturer    | PHOENIX CONTACT               |
| MPN / Reference | NS 35/ 7,5 PERF 2M NZ REF CUT |
| Catalog number  | 1210239                       |
| Category        | Mounting rail                 |
| Minimum order   | 25 Pcs                        |
| Document ID     | EO-833732F2BE                 |
| Generated       | 2026-08-03                    |

## Product Overview

DIN rail perforated

Symmetrical perforated rail, according to EN 60715, material:Steel, galvanized, thick layer passivation, Standard profile, color:silver, Packaging variant with 25 units (50 m)

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                  |
|--------------|----------------------------------|
| Catalog path | PHOENIX CONTACT > CABINET add-on |
|--------------|----------------------------------|

## Additional Product Information

Key Commercial Data

Orderkey 1210239

Packing unit 5 pc

Minimum order quantity 5 pc

Note Made to Order (non-returnable)

GTIN 4046356528580

Weight per Piece (excluding packing) 660.000 g

Custom tariff number 72166190

Country of origin DE (Germany)

Dimensions

Height 7.5 mm

Length 2000 mm

Width 35 mm

Hole width 15.00 mm

Hole height 6.20 mm

Drill hole spacing 25.00 mm

General

Material Steel

Coating galvanized

Color silver

Max. permissible thermal nominal current for PEN function 150.00 A

Standards and Regulations

Test standard acc. to EN 60715

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 4.027110804eCl@ss 4.127110804eCl@ss 5.027141143eCl@ss 5.127141100eCl@ss 6.027400600eCl@ss  
7.027400602eCl@ss 8.027400602eCl@ss 9.027400602

ETIM 2.0EC001285ETIM 3.0EC001285ETIM 4.0EC000212ETIM 5.0EC000212ETIM 6.0EC001285

UNSPSC 6.0130212109UNSPSC 7.090139121708UNSPSC 1139121708UNSPSC 12.0139121708UNSPSC  
13.239121708

ETIM for 1210239 Power distribution systems (EC001285)

Feature Name

Feature Value

Material (EF002169)

Steel

Surface protection (EF000139)

Other

Punch shape (EF001457)

Long-slot

Drill hole distance centrically (EF002677)

25 mm

Material thickness (EF000386)

1 mm

Length (EF001438)

2000 mm

Height (EF000040)

7.5 mm

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / NS 35/ 7,5 PERF 2M NZ REF CUT with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.