

INDUSTRIAL COMPONENT DATA

P-FU-FSI/C 5X20 1446149 PHOENIX CONTACT Fuse head, Before replacing the fuse, remove the fuse head from the ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: P-FU-FSI/C 5X20



Manufacturer	PHOENIX CONTACT
MPN / Reference	P-FU-FSI/C 5X20
Catalog number	1446149
Category	Component plug terminal block
Minimum order	10 Pcs
Document ID	EO-C953BD35AD
Generated	2026-08-05

Product Overview

Fuse head, Before replacing the fuse, remove the fuse head from the base terminal., rated voltage: 400 V, rated current: 6.3 A, fuse type: G/5 x 20, mounting class: Snap mounting, color: black

Fuse head, Before replacing the fuse G, remove the fuse head from the base terminal block

Fuse plug, Prior to replacing the fuse, disconnect the fuse plug from the basic terminal block., nom. voltage: 400 V, nominal current: 6.3 A, fuse type: G / 5 x 20, mounting type: Plug-in mounting, color: black

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs
--------------	-------------------------------

Additional Product Information

Technical dataNotesGeneral Prior to replacing the fuse, disconnect the fuse plug from the basic terminal block.

Product propertiesProduct type Fuse

Pitch 5.2 mm

Insulation characteristics

Overvoltage category III

Degree of pollution 3

Electrical propertiesFuse G / 5 x 20

Connection dataNominal current 6.3 A (the current is determined by the fuse used)

Maximum load current 6.3 A (the current is determined by the fuse used)

Nominal voltage 400 V (the voltage is determined by the fuse used)

DimensionsWidth 6.2 mm

Height 25 mm
Depth 58 mm
Length 25 mm
Pitch 5.2 mm
Material specifications Color black
Flammability rating according to UL 94 V0
Insulating material PA
Static insulating material application in cold -60 °C
Relative insulation material temperature index (Elec., UL 746 B) 130 °C
Fire protection for rail vehicles (DIN EN 45545-2) R22 HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R23 HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R24 HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R26 HL 1 - HL 3
Surface flammability NFPA 130 (ASTM E 162) passed
Specific optical density of smoke NFPA 130 (ASTM E 662) passed
Smoke gas toxicity NFPA 130 (SMP 800C) passed
Environmental and real-life conditions Ambient conditions
Ambient temperature (operation) -60 °C ... 105 °C (max. short-term operating temperature RTI Elec.)
Ambient temperature (storage/transport) -25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)
Ambient....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / P-FU-FSI/C 5X20 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.