

INDUSTRIAL COMPONENT DATA

PACT RCP-D190 2904892 PHOENIX CONTACT Coil

Brand: PHOENIX CONTACT | Manufacturer Part Number: PACT RCP-D190



Manufacturer	PHOENIX CONTACT
MPN / Reference	PACT RCP-D190
Catalog number	2904892
Category	Accessories/spare parts for low-voltage switch technology
Minimum order	1 Pcs
Document ID	EO-797F236BC1
Generated	2026-08-06

Product Overview

Coil

Rogowski coil with a length of 600 mm. The diameter of the measuring coil in installed state is 190 mm. The Rogowski coil is used for the measurement of AC current from busbars and high-voltage lines.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > INTERFACE Components (IF)

Additional Product Information

Key Commercial Data

Orderkey 2904892

Packing unit 1 pc

Note Made to Order (non-returnable)

GTIN 4046356898195

Weight per Piece (excluding packing) 181.500 g

Custom tariff number 90309000

Country of origin IT (Italy)

Measuring coil input data

Frequency measuring range 40 Hz ... 20000 Hz

Position error < 1 %

Linearity error 0.1 %

Measuring coil signal output

Output signal (at 50 Hz) 100 mV (no load, at 1,000 A)

Output voltage (in no-load operation) $V_{OUT} = M \cdot dI/dt$

Output voltage (sinusoidal, in no-load operation) 100 mV ($V_{OUT} = 2 \cdot \pi \cdot M \cdot f \cdot I$ ($M = 0.318 \mu H$; example: At 50 Hz; $I = 1,000 A$))

General data, measuring coil

Length of measuring coil 600 mm

Diameter of measuring coil 8.3 mm ± 0.2 mm

Length of signal cable 3000 mm

Conductor structure signal line 2x 0.22 mm (Signal (tinned))

1x 0.22 mm (Shielding (tinned))

Coil material Elastollan

Housing material PC

Insulation double insulation

Rated insulation voltage 1000 V AC (rms CAT III)

600 V AC (rms CAT IV)

Test voltage 10.45 kV (DC / 1 min.)

Basic accuracy

UL, USA/Canada UL 61010 Recognized

General data

Standards/regulations IEC 61010-1

IEC 61010-2-032

Standards and Regulations

Standards/regulations IEC 61010-1

IEC 61010-2-032

UL, USA/Canada UL 61010 Recognized

Ambient conditions

Ambient temperature (operation) -30 °C ... 80 °C (Measuring coil)

Ambient temperature (storage/transport) -40 °C ... 80 °C (Measuring coil)

Maximum altitude < 2000 m

Measuring coil degree of protection IP67 (not assessed by UL)

Environmental Product C...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PACT RCP-D190 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.