

INDUSTRIAL COMPONENT DATA

PAIS-4-FIX GN 3032801 PHOENIX CONTACT Test adapter

Brand: PHOENIX CONTACT | Manufacturer Part Number: PAIS-4-FIX GN



Manufacturer	PHOENIX CONTACT
MPN / Reference	PAIS-4-FIX GN
Catalog number	3032801
Category	Test plug for terminal blocks
Minimum order	10 Pcs
Document ID	EO-E1C36A80BB
Generated	2026-08-01

Product Overview

Test adapter

Test adapter, In plugged in state, safe against finger contact against unintentional direct contact according to DIN EN 50274, for 4 mm test pins and 5.2 mm, 6.2 mm and 8.2 mm pitch terminals, number of poles: 1, color: green

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs
--------------	-------------------------------

Additional Product Information

Key Commercial Data

Orderkey 3032801

Packing unit 10 pc

Minimum order quantity 10 pc

Note Made to Order (non-returnable)

GTIN 4055626369358

Weight per Piece (excluding packing) 2.350 g

Custom tariff number 85366990

Country of origin PL (Poland)

Dimensions

Height 51.5 mm

Length 5.8 mm

Width 5.8 mm

Diameter 5.8 mm

Pin diameter 2.4 mm

General

Note Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in

Do not plug in while the power is connected

Latching testing accessories, therefore only suitable for being plugged in once

Color green

Material Copper

Ambient temperature (operation) -40 °C ... 125 °C

Max. voltage 250 V

Maximum load current 10 A

Insertion/withdrawal cycles 1

Standards and Regulations

Flammability rating according to UL 94 V0

Fire protection for rail vehicles (DIN EN 45545-2) R22 HL 1 - HL 3

Fire protection for rail vehicles (DIN EN 45545-2) R23 HL 1 - HL 3

Fire protection for rail vehicles (DIN EN 45545-2) R24 HL 1 - HL 3

Fire protection for rail vehicles (DIN EN 45545-2) R26 HL 1 - HL 3

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss 4.027141127eCl@ss 4.127141127eCl@ss 5.027141127eCl@ss 5.127141100eCl@ss 6.027141100eCl@ss

7.027141148eCl@ss 8.027141148eCl@ss 9.027141148

ETIM 2.0EC000897ETIM 3.0EC000897ETIM 4.0EC002255ETIM 5.0EC002255ETIM 6.0EC00...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PAIS-4-FIX GN with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.