

INDUSTRIAL COMPONENT DATA

SACC-4P-DSI-M12FSD/FSD-M16 1424326 PHOENIX CONTACT

Panel feed-through

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACC-4P-DSI-M12FSD/FSD-M16



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACC-4P-DSI-M12FSD/FSD-M16
Catalog number	1424326
Category	Circular connector, mounting (without cable)
Minimum order	1 Pcs
Document ID	EO-5B3605BF77
Generated	2026-08-04

Product Overview

Panel feed-through

Conect. plug. to be apar. Wall Poster., 4-Pole, Female Connection, Straight, M12, D-Data, A Female Straight Connection
M12, D-Data, Bipolar Mount, M16 x 1.5

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data

Orderkey 1424326

Packing unit 1 pc

Catalog page Page 48 (C-2-2017)

GTIN 4046356730525

Weight per Piece (excluding packing) 32.500 g

Custom tariff number 85366990

Country of origin DE (Germany)

Ambient conditions

Ambient temperature (operation) -25 °C ... 85 °C (Plug / socket)

Degree of protection IP67

General

Note The electrical and mechanical data specified assume that the connector pair is correctly locked and mounted. If the

connector is unlocked and if there is a danger of contamination, the connector must be sealed using a protective cap > IP54. Influences arising from litz wires, cables or PCB assembly must also be taken into consideration.

Rated current at 40°C 4 A

Rated voltage 60 V

Rated surge voltage 0.8 kV

Number of positions 4

Insulation resistance $\geq 100 \text{ M}\Omega$

Coding D - data

Standards/regulations M12 connector IEC 61076-2-101

Status display No

Overvoltage category II

Degree of pollution 3

Insertion/withdrawal cycles > 100

Torque 3 Nm ... 4 Nm (Installation-side)

Mounting type Bipolar mounting M16 x 1.5

Material

Flammability rating according to UL 94 HB

Contact material CuZn

Contact surface material Au

Contact carrier material PA 6.6

Material, knurls Nickel-plated brass

Sealing material FKM

Cable

Standards/specifications M12 connector IEC 61076-2-101

Ambient temperature (operation) -40 °C ... 85 °C (cable, fixed installation)

-25 °C ... 85 °C (cable, flexible installation)

Standards and Regulations

Standard designation M12 connector

Standards/reg...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACC-4P-DSI-M12FSD/FSD-M16 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.