

INDUSTRIAL COMPONENT DATA

SSL 2,5 3043815 PHOENIX CONTACT Panel feed-through

Brand: PHOENIX CONTACT | Manufacturer Part Number: SSL 2,5



Manufacturer	PHOENIX CONTACT
MPN / Reference	SSL 2,5
Catalog number	3043815
Category	Installation clamp for meters
Minimum order	50 Pcs
Document ID	EO-350C8547F6
Generated	2026-07-29

Product Overview

Panel feed-through

Feedthrough, width: 5.2 mm, colour: grey

Panel feed-through, width: 5.2 mm, color: gray

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs
--------------	-------------------------------

Additional Product Information

Technical dataProduct propertiesProduct type Mounting material

Data management status

Article revision 02

Insulation characteristics

Overvoltage category III

Electrical propertiesRated surge voltage 8.00 kV

DimensionsDimensional drawing

Width 5.2 mm

Plate thickness 0.8 mm ... 3 mm

Installation dimensions

Length of the assembly cutout 16.6 mm

Material specificationsColor gray (RAL 7042)

Material PA

Flammability rating according to UL 94 V0

Insulating material group I

Insulating material PA

Static insulating material application in cold -60 °C

Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 130 °C

Relative insulation material temperature index (Elec., UL 746 B) 130 °C

Fire protection for rail vehicles (DIN EN 45545-2) R22 HL 1 - HL 3

Fire protection for rail vehicles (DIN EN 45545-2) R23 HL 1 - HL 3

Fire protection for rail vehicles (DIN EN 45545-2) R24 HL 1 - HL 3

Fire protection for rail vehicles (DIN EN 45545-2) R26 HL 1 - HL 3

Calorimetric heat release NFPA 130 (ASTM E 1354) 28 MJ/kg

Surface flammability NFPA 130 (ASTM E 162) passed

Specific optical density of smoke NFPA 130 (ASTM E 662) passed

Smoke gas toxicity NFPA 130 (SMP 800C) passed

Environmental and real-life conditions Ambient conditions

Ambient temperature (operation) -60 °C ... 105 °C (max. short-term operating temperature RTI Elec.)

Ambient temperature (storage/transport) -25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)

Ambient temperature (assembly) -5 °C ... 70....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SSL 2,5 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.