

INDUSTRIAL COMPONENT DATA

QPD W 4PE6,0 12-20 M25 0,5 GY 1410401 PHOENIX CONTACT

Panel feed-through

Brand: PHOENIX CONTACT | Manufacturer Part Number: QPD W 4PE6,0 12-20 M25 0,5 GY



Manufacturer	PHOENIX CONTACT
MPN / Reference	QPD W 4PE6,0 12-20 M25 0,5 GY
Catalog number	1410401
Category	Sensor-actuator connector chassis
Minimum order	1 Pcs
Document ID	EO-E679062119
Generated	2026-08-06

Product Overview

Panel feed-through

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > QUICKON Installation System (QPD)

Additional Product Information

Key Commercial Data

Orderkey 1410401

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 193 (NTK-2014)

GTIN 4046356929417

Weight per Piece (excluding packing) 247.500 g

Custom tariff number 85366990

Country of origin PL (Poland)

General

Type QPD 5x6,0

Length of cable 0.5 m

Color gray

Locking type Screw locking

Connection method QUICKON connection

IDC connection

Number of positions 5

Note number of positions 4+PE

Wrench size, union nut 30 mm

Tightening torque, union nut 15 Nm

Number of connections 10

Conductor cross section flexible min. 2.5 mm²

Conductor cross section flexible max. 6 mm²

Conductor cross section solid min. 2.5 mm²

Conductor cross section solid max. 6 mm²

Conductor cross section AWG min. 14

Conductor cross section AWG max. 10

Cable

Structure of individual litz in acc. with VDE 0295 / smallest wire diameter VDE 0295 class 1 to 6/min. 0.15 mm

Wire insulation material PVC/PE/TPE/rubber

Wire diameter including insulation 2.95 mm ... 5 mm

External cable diameter 12 mm ... 20 mm

Conductor cross section 6 mm²

Wire colors black, brown, gray, blue, green/yellow

Position marking 1, 2, L, N, PE

Ambient conditions

Degree of protection IP66

IP68 (2 m / 24 h)

IP69K

Ambient temperature (operation) -40 °C ... 100 °C

Ambient temperature (storage/transport) -40 °C ... 100 °C

Temperature when conductor connected -5 °C ... 50 °C

Electrical characteristics

Nominal current I_N 40 A

Rated current 40 A

Rated voltage (III/3) 690 V

Rated voltage (III/2) 1000 V

Rated...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / QPD W 4PE6,0 12-20 M25 0,5 GY with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.