

INDUSTRIAL COMPONENT DATA

ST-17S1N8ACK02S 1618834 PHOENIX CONTACT Panel feed-through

Brand: PHOENIX CONTACT | Manufacturer Part Number: ST-17S1N8ACK02S



Manufacturer	PHOENIX CONTACT
MPN / Reference	ST-17S1N8ACK02S
Catalog number	1618834
Category	Circular connector, mounting (without cable)
Minimum order	1 Pcs
Document ID	EO-86C1CA83D3
Generated	2026-08-05

Product Overview

Panel feed-through

Cable pass-through, straight, SPEEDCON lock, M17, number of poles: 17, contact type: Female, Flat joint, 4x Ø 3.2, shielded: yes, flange size: 25.75 mm x 25.75 mm, protection index: IP67, cable diameter range: 3.5 mm ... 5.5 mm, number of poles: 17, connection type: Crimped connection, series: ST

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data

Orderkey 1618834

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 62 (C-2-2017)

GTIN 4046356817196

Weight per Piece (excluding packing) 44.140 g

Custom tariff number 85366990

Country of origin DE (Germany)

General

Type of locking SPEEDCON locking

Direction of rotation of contact chamber numbering Standard

Coding N

Contact connection method Crimp connection

Type of contacts Socket

Number of positions 17

Contact diameter of power contacts 0.6 mm

Nominal current per power contact at 25°C 3.6 A

Conductor entry 3.5 mm ... 5.5 mm

Pg housing screw connection none

Mounting type 4x Ø 3.2

Ambient conditions

Ambient temperature -40 °C ... 125 °C

Degree of protection IP67

Specifications according to DIN EN 61984:2001

Nominal / operating voltage of power contacts 60 V

Rated surge voltage of power contacts 1.5 kV

Overvoltage category of power contacts II

Degree of pollution of power contacts 3

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027279200eCl@ss
7.027440103eCl@ss 8.027440103eCl@ss 9.027440102

ETIM 3.0EC001121ETIM 4.0EC002635ETIM 5.0EC002061ETIM 6.0EC002061

UNSPSC 6.0143172015UNSPSC 7.090143201404UNSPSC 1143172015UNSPSC 12.0143201404UNSPSC
13.239121413

ETIM for 1618834 Connectors (...)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ST-17S1N8ACK02S with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.