

INDUSTRIAL COMPONENT DATA

PWO 4-POT-SCM/S 3056925 PHOENIX CONTACT Panel feed-through terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: PWO 4-POT-SCM/S



Manufacturer	PHOENIX CONTACT
MPN / Reference	PWO 4-POT-SCM/S
Catalog number	3056925
Category	Panel feed-through terminal block
Minimum order	50 Pcs
Document ID	EO-E8F2712535
Generated	2026-08-01

Product Overview

Panel feed-through terminal block

Terminal block, connection type: Push-in spring connection, Flat plug connection, number of poles: 1, charging current: 18 A, cross-section: 0.2 mm² - 4 mm², conductor connection direction with respect to the plug direction: 45 °, width: 8.1 mm

Panel feed-through terminal block, connection method: Push-in spring connection, Spade connection, number of positions: 1, load current: 18 A, cross section: 0.2 mm² - 4 mm², connection direction of the conductor to plug-in direction: 45 °, width: 8.1 mm, color: gray

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Technical dataProduct propertiesProduct type Panel feed-through terminal block

Product family PWO 4-POT-SCM

Number of positions 1

Pitch 8.1 mm

Number of connections 2

Number of rows 1

Number of potentials 1

Potentials 1

Data management status

Article revision 03

Insulation characteristics

Overvoltage category III

Degree of pollution 3

Electrical propertiesNominal current I_N 18 A

Nominal voltage U_N 800 V

Rated voltage (III/3) 800 V

Rated surge voltage (III/3) 8 kV

Connection dataConnection technology

Connector system PW 4

Nominal cross section 4 mm²

Conductor connection exterior

Connection method Push-in spring connection

Connection direction of the conductor to plug-in direction 45 °

Conductor cross section rigid 0.2 mm² ... 4 mm²

Conductor cross section flexible 0.2 mm² ... 6 mm²

Conductor cross section flexible, with ferrule without plastic sleeve 0.25 mm² ... 6 mm²

Conductor cross section, flexible, with ferrule, with plastic sleeve 0.25 mm² ... 4 mm²

2 conductors with the same cross section, flexible, with TWIN ferrule with plastic sleeve 0.5 mm² ... 1 mm²

Internal cylindrical gage A4

Stripping length 10 mm

Conductor connection interior

Connection method Spade connection

Connection direction of the conductor to plug-in direction 0 °

MountingAttachment to feed-through panel

Tightening torque 0.5 Nm ... 0.6 Nm (Mounting screw torque)

Material specificationsMaterial data - contact

Note WEEE/RoHS-compliant, free of whiskers according to IEC 60068-2-82/JEDEC JESD 201

Contact...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PWO 4-POT-SCM/S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.