

INDUSTRIAL COMPONENT DATA

DFK 4 0708357 PHOENIX CONTACT Panel feed-through terminal block, Connection method: Screw connection, Solder..

Brand: PHOENIX CONTACT | Manufacturer Part Number: DFK 4



Manufacturer	PHOENIX CONTACT
MPN / Reference	DFK 4
Catalog number	0708357
Category	Panel feed-through terminal block
Minimum order	50 Pcs
Document ID	EO-26EAE0191D
Generated	2026-08-01

Product Overview

Panel feed-through terminal block, Connection method: Screw connection, Solder/Slip-on connection, Load current : 18 A, Cross section: 0.2 mm²

Terminal block, connection type: Screw connection with traction capsule, Welding/flat plug connection, number of poles: 1, charging current: 18 A, cross-section: 0.2 mm² - 6 mm², conductor connection direction with respect to the plug direction: 90 °, width: 6.15 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

General

Number of levels 1

Number of connections 2

Nominal cross section 1.5 mm²

Color gray

Insulating material PA

Flammability rating according to UL 94 V2

General

Rated surge voltage 4 kV

Pollution degree 3

Overvoltage category III

Insulating material group I

Connection in acc. with standard IEC 60947-7-1

Nominal current IN 17.5 A

Maximum load current 17.5 A

Nominal voltage UN 400 V

Open side panel nein

Number of positions 0

Dimensions

Width 6.2 mm

Length 39 mm

Plate thickness 1.5 mm

Connection data

Connection side Outside

Connection method Screw connection

Conductor cross section solid min. 0.2 mm²

Conductor cross section solid max. 6 mm²

Conductor cross section flexible min. 0.2 mm²

Conductor cross section flexible max. 4 mm²

Conductor cross section AWG min. 24

Conductor cross section AWG max. 10

Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule without plastic sleeve max. 4 mm²

Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule with plastic sleeve max. 2.5 mm²

2 conductors with same cross section, solid min. 0.2 mm²

2 conductors with same cross section, solid max. 1.5 mm²

2 conductors with same cross section, stranded min. 0.2 mm²

2 conductors with same cross section, stranded max. 1.5 mm²

2 conductors with same cross section, stranded, ferrules without plastic sleeve, min. 0.25 mm²

2 conductors with same cross sec...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / DFK 4 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.