

INDUSTRIAL COMPONENT DATA

UWV 10 3073403 PHOENIX CONTACT Panel feed-through terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UWV 10



Manufacturer	PHOENIX CONTACT
MPN / Reference	UWV 10
Catalog number	3073403
Category	Panel feed-through terminal block
Minimum order	50 Pcs
Document ID	EO-FE7EC1DF3B
Generated	2026-08-02

Product Overview

Panel feed-through terminal block

Terminal block, connection type: Screw connection with traction capsule, Screw connection with traction capsule, number of poles: 1, load current: 57 A, cross-section: 0.5 mm² - 16 mm², conductor connection direction with respect to the plug direction: -90 °, width: 10.1 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data

Orderkey 3073403

Packing unit 50 pc

Note Made to Order (non-returnable)

Catalog page Page 611 (C-1-2013)

GTIN 4046356344715

Weight per Piece (excluding packing) 18.500 g

Custom tariff number 85369010

Country of origin CN (China)

General

Number of levels 1

Number of connections 2

Nominal cross section 10 mm²
Color gray
Insulating material PA
Flammability rating according to UL 94 V0
Rated surge voltage 6 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Connection in acc. with standard IEC 60947-7-1
Nominal current I_N 57 A
Maximum load current 76 A
Nominal voltage U_N 500 V (with spacer plate)
Open side panel No
Number of positions 1
Dimensions
Width 10.1 mm
Pitch 10.1 mm
Plate thickness 1 mm ... 4 mm
Connection data
Connection side outside
Connection method Screw connection
Conductor cross section solid min. 0.5 mm²
Conductor cross section solid max. 16 mm²
Conductor cross section flexible min. 0.5 mm²
Conductor cross section flexible max. 10 mm²
Conductor cross section AWG min. 20
Conductor cross section AWG max. 6
Conductor cross section flexible, with ferrule without plastic sleeve min. 0.5 mm²
Conductor cross section flexible, with ferrule without plastic sleeve max. 10 mm²
Conductor cross section flexible, with ferrule with plastic sleeve min. 0.5 mm²
Conductor cross section flexible, with ferrule with plastic sleeve max. 10 mm²
2 conductors with same cross section, solid min. 0.5 mm²
2 conductors with same cross section, s...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UWV 10 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.