

INDUSTRIAL COMPONENT DATA

VS-PPC-F1-SCRJ-MNNA-1RF 1405374 PHOENIX CONTACT

Panel mounting frames

Brand: PHOENIX CONTACT | Manufacturer Part Number: VS-PPC-F1-SCRJ-MNNA-1RF



Manufacturer	PHOENIX CONTACT
MPN / Reference	VS-PPC-F1-SCRJ-MNNA-1RF
Catalog number	1405374
Category	Fixing element for industrial connectors
Minimum order	1 Pcs
Document ID	EO-AB00639DF9
Generated	2026-08-03

Product Overview

Panel mounting frames

Recessed frame SC-RJ, IP67, for Push-Pull locking, metallic, with Freenet system, for rectangular mounting section, with gasket and SC-RJ coupling (for POF, PCF & GOF), without fixing screws

SC-RJ panel mounting frame, IP67, for push-pull interlocking, metal, with Freenet system, for rectangular mounting cutout, with seal and SC-RJ coupling (for POF, PCF, and GOF), without mounting screws

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Technical dataProduct propertiesProduct type Panel-mount frame

Application Freenet

Type SC-RJ

Number of positions 2

Connection profile SC-RJ

Type SC-RJ

Cable outlet straight

Data management status

Article revision 04

Insulation characteristics

Degree of pollution 2

Electrical propertiesTransmission medium FO

Connection dataConnection technology

Connection method Push-Pull

DimensionsDimensional drawing

Width 22.2 mm

Height 42 mm

Mechanical characteristics

Ferrule diameter 2.50 mm

Material specificationsColor silver

Material Metal

Flammability rating according to UL 94 V0

Housing material Metal

Housing surface material nickel-plated

Cable/lineResistance to oil yes

Flame resistance yes

FO cable

Number of fibers 2

Fiber POF, PCF, GOF

Fiber type GOF, PCF, POF

Transmission medium FO

Mechanical propertiesMechanical data

Insertion/withdrawal cycles ≥ 500

Environmental and real-life conditionsAmbient conditions

Degree of protection IP67 (IP65/67)

IP65/IP67

Ambient temperature (operation) -40 °C ... 70 °C

Ambient temperature (storage/transport) -40 °C ... 70 °C

Ambient temperature (assembly) 0 °C ... 50 °C

Resistance to oil yes

Standards and regulationsFlame resistance yes

Resistance to oil yes

MountingMounting type Wall mounting

ETIM for 1405374 Connectors (EC002310)

Feature Name

Feature Value

Material assembly frame (EF007542)

Other

With PE-connection (EF005600)

No

Inflammability class of insulation material according to UL94 (EF002521)

V0

Fixing direction (EF012208)

Swivelling

Widt...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VS-PPC-F1-SCRJ-MNNA-1RF with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.