

**INDUSTRIAL COMPONENT DATA**

# UM-ALU 4-100,5 FRONT 60 2200944 PHOENIX CONTACT

## Components of electronic housing

Brand: PHOENIX CONTACT | Manufacturer Part Number: UM-ALU 4-100,5 FRONT 60



|                 |                                  |
|-----------------|----------------------------------|
| Manufacturer    | PHOENIX CONTACT                  |
| MPN / Reference | UM-ALU 4-100,5 FRONT 60          |
| Catalog number  | 2200944                          |
| Category        | Extruded profile modular housing |
| Minimum order   | 1 Pcs                            |
| Document ID     | EO-CCAB271B85                    |
| Generated       | 2026-08-02                       |

## Product Overview

Components of electronic housing

Extruded profile boxes, Front plate with basic profile, color: aluminum color, width: 101.8 mm, length: 61.3 mm, depth: 2 mm, recommended for UM-ALU 4 side elements-.. COVER PA..

Press-drawn section housings, Basic profile front plate, width: 101.8 mm, length: 61.3 mm, depth: 2 mm, recommended for UM-ALU 4-..COVER PA.. lateral elements

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                |
|--------------|--------------------------------|
| Catalog path | PHOENIX CONTACT > Housing (HS) |
|--------------|--------------------------------|

## Additional Product Information

Technical dataProduct propertiesProduct type Component housing cover

Housing type Press-drawn section housings

Housing series UM-ALU

Product family UM-ALU 4-100,5

Type Basic profile front plate

Ventilation openings present no

DimensionsWidth 101.8 mm

Depth 2 mm

Length 61.3 mm

Material specificationsColor (Housing) Aluminum color

Housing material Aluminum

Surface characteristics anodized  
Environmental and real-life conditions Ambient conditions  
Max. IP code to attain IP40  
Ambient temperature (operation) -40 °C ... 100 °C (depending on power dissipation)  
Ambient temperature (storage/transport) -40 °C ... 55 °C  
Ambient temperature (assembly) -5 °C ... 100 °C  
ETIM for 2200944 Low-voltage industrial controls and switchgear (EC002779)  
Feature Name  
Feature Value  
Type of enclosure (EF003086)  
Open  
Housing connectable (EF003088)  
No  
Suitable for rail mounting (EF003972)  
No  
Wall mounting possible (EF003973)  
No  
With integrated PCB-mounting connection system (EF003087)  
No  
Material (EF002169)  
Aluminium  
Surface finishing (EF006569)  
Other  
Colour (EF000007)  
Other

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UM-ALU 4-100,5 FRONT 60 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.