

INDUSTRIAL COMPONENT DATA

ME 22,5 F-UTG BUS/ 5+2 GN 2706027 PHOENIX CONTACT

Mounting base housing

Brand: PHOENIX CONTACT | Manufacturer Part Number: ME 22,5 F-UTG BUS/ 5+2 GN



Manufacturer	PHOENIX CONTACT
MPN / Reference	ME 22,5 F-UTG BUS/ 5+2 GN
Catalog number	2706027
Category	Extruded profile modular housing
Minimum order	10 Pcs
Document ID	EO-FFE993DBD5
Generated	2026-08-06

Product Overview

Mounting base housing

Rail box, Lower part of the housing with metal pin, flat design, without ventilation slits, width: 22.6 mm, height: 99 mm, depth: 84.8 mm, color: green (6021), cross bridge: integrated bus connector, number of poles cross connector: 5+2, Bus connector: 5 parallel contacts, 2 series contacts

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Housing (HS)**

Additional Product Information

Key Commercial Data

Orderkey 2706027

Packing unit 10 pc

Note Made to Order (non-returnable)

Catalog page Page 663 (C-1-2013)

GTIN 4017918820961

Weight per Piece (excluding packing) 37.250 g

Custom tariff number 85369010

Country of origin DE (Germany)

General

Housing type Component housing

Housing material Polyamide

Color (RAL) green

Ambient conditions

Ambient temperature (storage/transport) -40 °C ... 70 °C

Ambient temperature (assembly) -5 °C ... 100 °C

Ambient temperature (operation) -40 °C ... 105 °C (depending on power dissipation)

Dimensions

Length 99 mm

Height 106 mm

Width 22.5 mm

Depth 99 mm

102 mm

Technical data

Connection in acc. with standard CUL

Nominal voltage UN 300 V

Nominal current IN 8 A

Indicator1 CUL1

Power dissipation without gap 5.5 W

Power dissipation with 20 mm gap 9.6 W

Number of positions 16

24

Standards and Regulations

Connection in acc. with standard CUL

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 4.027180401eCl@ss 4.127180401eCl@ss 5.027180506eCl@ss 5.127180500eCl@ss 6.027180800eCl@ss
7.027182702eCl@ss 8.027182702eCl@ss 9.027182702

ETIM 2.0EC001031ETIM 3.0EC001031ETIM 4.0EC001031ETIM 5.0EC001031ETIM 6.0EC001031

UNSPSC 6.0131261501UNSPSC 7.090131261501UNSPSC 1131261501UNSPSC 12.0131261501UNSPSC
13.231261501

ETIM for 2706027 Low-voltage industrial controls and switchgear (EC002779)

Fea...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ME 22,5 F-UTG BUS/ 5+2 GN with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.