

INDUSTRIAL COMPONENT DATA

ATP-STTB 4 3030747 PHOENIX CONTACT Partition plate

Brand: PHOENIX CONTACT | Manufacturer Part Number: ATP-STTB 4



Manufacturer	PHOENIX CONTACT
MPN / Reference	ATP-STTB 4
Catalog number	3030747
Category	Endplate and partition plate for terminal block
Minimum order	50 Pcs
Document ID	EO-0E1EC854BC
Generated	2026-08-03

Product Overview

Partition plate

Spacer plate, length: 88.7 mm, width: 2 mm, height: 53 mm, colour: grey

Partition plate, depth: 53 mm, width: 2 mm, height: 88.7 mm, color: gray

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs
--------------	-------------------------------

Additional Product Information

Technical dataProduct propertiesProduct type Partition plate

Data management status

Article revision 02

DimensionsWidth 2 mm

Height 88.7 mm

Depth 53 mm

Material specificationsColor gray (RAL 7042)

Material PA

Flammability rating according to UL 94 V0

Static insulating material application in cold -60 °C

Relative insulation material temperature index (Elec., UL 746 B) 130 °C

Fire protection for rail vehicles (DIN EN 45545-2) R22 HL 1 - HL 3

Fire protection for rail vehicles (DIN EN 45545-2) R23 HL 1 - HL 3

Fire protection for rail vehicles (DIN EN 45545-2) R24 HL 1 - HL 3

Fire protection for rail vehicles (DIN EN 45545-2) R26 HL 1 - HL 3

Surface flammability NFPA 130 (ASTM E 162) passed

Specific optical density of smoke NFPA 130 (ASTM E 662) passed

Smoke gas toxicity NFPA 130 (SMP 800C) passed

Environmental and real-life conditions Ambient conditions

Ambient temperature (operation) -60 °C ... 110 °C (Operating temperature range incl. self-heating; for max. short-term operating temperature, see RTI Elec.)

Ambient temperature (storage/transport) -25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)

Ambient temperature (assembly) -5 °C ... 70 °C

Ambient temperature (actuation) -5 °C ... 70 °C

Permissible humidity (operation) 20 % ... 90 %

Permissible humidity (storage/transport) 30 % ... 70 %

ETIM for 3030747 Terminal blocks (EC000886)

Feature Name

Feature Value

End plate model (EF006586)

No

Partition model (EF006587)

Yes

Colour (EF000007)

Grey

Thickness (EF00...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ATP-STTB 4 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.