

**INDUSTRIAL COMPONENT DATA**

# ATP-UT-TWIN 3047183 PHOENIX CONTACT Partition plate

Brand: PHOENIX CONTACT | Manufacturer Part Number: ATP-UT-TWIN



|                 |                                                 |
|-----------------|-------------------------------------------------|
| Manufacturer    | PHOENIX CONTACT                                 |
| MPN / Reference | ATP-UT-TWIN                                     |
| Catalog number  | 3047183                                         |
| Category        | Endplate and partition plate for terminal block |
| Minimum order   | 50 Pcs                                          |
| Document ID     | EO-29762943E9                                   |
| Generated       | 2026-08-03                                      |

## Product Overview

Partition plate

Spacer plate, length: 62.1 mm, width: 2.2 mm, height: 52.5 mm, colour: grey

Partition plate, depth: 52.5 mm, width: 2.2 mm, height: 62.1 mm, color: gray

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                               |
|--------------|-------------------------------|
| Catalog path | PHOENIX CONTACT > Modular TBs |
|--------------|-------------------------------|

## Additional Product Information

Technical dataProduct propertiesProduct type Partition plate

Data management status

Article revision 01

DimensionsWidth 2.2 mm

Height 62.1 mm

Depth 52.5 mm

Material specificationsColor gray (RAL 7042)

Material PA

Flammability rating according to UL 94 V0

Static insulating material application in cold -60 °C

Relative insulation material temperature index (Elec., UL 746 B) 130 °C

Fire protection for rail vehicles (DIN EN 45545-2) R22 HL 1 - HL 3

Fire protection for rail vehicles (DIN EN 45545-2) R23 HL 1 - HL 3

Fire protection for rail vehicles (DIN EN 45545-2) R24 HL 1 - HL 3

Fire protection for rail vehicles (DIN EN 45545-2) R26 HL 1 - HL 3

Surface flammability NFPA 130 (ASTM E 162) passed

Specific optical density of smoke NFPA 130 (ASTM E 662) passed

Smoke gas toxicity NFPA 130 (SMP 800C) passed

Environmental and real-life conditions Ambient conditions

Ambient temperature (operation) -60 °C ... 110 °C (Operating temperature range incl. self-heating; for max. short-term operating temperature, see RTI Elec.)

Ambient temperature (storage/transport) -25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)

Ambient temperature (assembly) -5 °C ... 70 °C

Ambient temperature (actuation) -5 °C ... 70 °C

Permissible humidity (operation) 20 % ... 90 %

Permissible humidity (storage/transport) 30 % ... 70 %

ETIM for 3047183 Terminal blocks (EC000886)

Feature Name

Feature Value

End plate model (EF006586)

No

Partition model (EF006587)

Yes

Colour (EF000007)

Grey

Thickness (...)

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ATP-UT-TWIN with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.