

INDUSTRIAL COMPONENT DATA

FL ISOLATOR 100-M12 2902985 PHOENIX CONTACT Network isolator

Brand: PHOENIX CONTACT | Manufacturer Part Number: FL ISOLATOR 100-M12



Manufacturer	PHOENIX CONTACT
MPN / Reference	FL ISOLATOR 100-M12
Catalog number	2902985
Category	Accessories/spare parts for controls
Minimum order	1 Pcs
Document ID	EO-7B73CD40CD
Generated	2026-08-01

Product Overview

Network isolator

Passive network isolator e.g. galvanic separation in Ethernet networks. To protect Ethernet devices against potential differences up to 4 kV. Attachable for sending ranges up to 100 Mbits/s. Ethernet connection via two connected females. M12 (coded D).

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Safety
--------------	--------------------------

Additional Product Information

Key Commercial Data

Orderkey 2902985

Packing unit 1 pc

Catalog page Page 345 (C-6-2017)

GTIN 4046356727815

Weight per Piece (excluding packing) 155.000 g

Custom tariff number 85437090

Country of origin DE (Germany)

Note

Utilization restriction EMC: class A product, see manufacturer's declaration in the download area

Dimensions

Dimensional drawing

Width 66 mm

Height 91 mm

Depth 34 mm

Ambient conditions

Ambient temperature (operation) -40 °C ... 75 °C (85°C for 10 min.; thereafter function can no longer be guaranteed - check device)

Ambient temperature (storage/transport) -40 °C ... 75 °C

Permissible humidity (operation) 10 % ... 95 %

Permissible humidity (storage/transport) 5 % ... 95 %

Altitude 5000 m (For restrictions see manufacturer's declaration)

Degree of protection IP54

General

Electrical isolation Port X1//port X2

Test voltage data interface/data interface 4 kV AC (50 Hz, 1 min.)

Insulation voltage input/output 250 Vrms

Electromagnetic compatibility Conformance with EMC Directive 2014/30/EU

Mounting position Wall mounting

Net weight 155 g

Housing material Plastic, FR 2010

V0 (UL 94)

Color black

MTBF 38062 Years (Telcordia standard, 25°C temperature, 21% operating cycle (5 days a week, 8 hours a day))

12264 Years (Telcordia standard, 40°C temperature, 34.25% operating cycle (5 days a week, 12 hours a day))

MTTF 18372 Years (SN 29500 standard, temperature 25 °C, operating cycle 21 % (5 days a week, 8 hours a day))

13381 Years (SN 29500 standard, temperature 40 °C, opera...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FL ISOLATOR 100-M12 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.