

**INDUSTRIAL COMPONENT DATA**

# PSM PTK-4 2799364 PHOENIX CONTACT Connection distributor

Brand: PHOENIX CONTACT | Manufacturer Part Number: PSM PTK-4



|                 |                          |
|-----------------|--------------------------|
| Manufacturer    | PHOENIX CONTACT          |
| MPN / Reference | PSM PTK-4                |
| Catalog number  | 2799364                  |
| Category        | PLC communication module |
| Minimum order   | 1 Pcs                    |
| Document ID     | EO-03B0BF072C            |
| Generated       | 2026-08-03               |

## Product Overview

Connection distributor

RS-485 passive T-shunt, equipped with one 9-pole D-SUB male connector and five 9-pole D-SUB female connectors

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path      PHOENIX CONTACT &gt; Safety

## Additional Product Information

Key Commercial Data

Orderkey 2799364

Packing unit 1 pc

Catalog page Page 381 (C-6-2017)

GTIN 4017918074050

Weight per Piece (excluding packing) 146.200 g

Custom tariff number 85366990

Country of origin DE (Germany)

Dimensions

Width 89.8 mm

Height 89.6 mm

Length 39 mm

Ambient conditions

Ambient temperature (operation) -25 °C ... 70 °C

**General**

Nominal voltage UN 60 V AC/DC

Nominal current IN 1 A

Bus system RS-485

Shielding D-SUB frame

Test voltage 500 V AC (50 Hz, 1 min, rms)

Housing material PVC

Flammability rating according to UL 94 V0

Pin assignment all 1:1

**Connection data**

Connection Incoming

Number of positions 9

Connection method D-SUB 9 plug

Connection Outgoing

Number of positions 9

Connection method D-SUB-9 female connector

Connection Branching

Number of positions 9

Connection method 4 x D-SUB-9 socket

**Standards and Regulations**

Free from substances that could impair the application of coating according to P-VW 3.10.7 57 65 0 VW-AUDI-Seat central standard

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

**Classifications**

eCl@ss 4.027230207eCl@ss 4.127230207eCl@ss 5.027230207eCl@ss 5.127242700eCl@ss 6.027242200eCl@ss 7.027242208eCl@ss 8.027242208eCl@ss 9.027242208

ETIM 2.0EC001423ETIM 3.0EC001423ETIM 4.0EC001423ETIM 5.0EC001423ETIM 6.0EC001423

UNSPSC 6.0130211506UNSPSC 7.090139121008UNSPSC 1139121008UNSPSC 12.0139121008UNSPSC 13.2391221...

**REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW**Send PHOENIX CONTACT / PSM PTK-4 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.