

INDUSTRIAL COMPONENT DATA

VS-IP20/10G-IP20/10G-94F/5 1418879 PHOENIX CONTACT

Patch cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: VS-IP20/10G-IP20/10G-94F/5



Manufacturer	PHOENIX CONTACT
MPN / Reference	VS-IP20/10G-IP20/10G-94F/5
Catalog number	1418879
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-BC0A576BDE
Generated	2026-08-03

Product Overview

Patch cable

Patch cable, protection rating: IP20, cable length: 5 m, number of poles: 8, 10 GBit/s, CAT6A, Ethernet

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data

Orderkey 1418879

Packing unit 1 pc

Catalog page Page 406 (C-2-2017)

GTIN 4046356537988

Weight per Piece (excluding packing) 236.000 g

Custom tariff number 85444210

Country of origin DE (Germany)

Dimensions

Length of cable 5.00 m

Ambient conditions

Degree of protection IP20

Ambient temperature (operation) -25 °C ... 60 °C (RJ45 connector)

General data

Rated current at 40°C 0.5 A
Rated voltage 48 V
Number of positions 8
Alternative short product description Patch cable
Cable
Cable type Ethernet 10 Gbit
Cable type (abbreviation) 94F
UL AWM style 20963 (80°C/30 V)
Signal type/category Ethernet CAT6A, 10 Gbps
Cable structure 4x2xAWG26/7; S/FTP
Conductor cross section 4x 2x 0.14 mm²
AWG signal line 26
Conductor structure signal line 7x 0.16 mm
Core diameter including insulation 1.04 mm
Wire colors white/blue-blue, white/orange-orange, white/green-green, white/brown-brown
Twisted pairs 2 cores to the pair
Type of pair shielding Aluminum-lined foil
Overall twist 4 pairs for core
Shielding Tinned copper braided shield
Optical shield covering 70 %
External sheath, color water blue RAL 5021
Outer sheath thickness 0.65 mm
External cable diameter D 6.4 mm ±0.2 mm
Minimum bending radius, fixed installation 4 x D
Minimum bending radius, flexible installation 8 x D
Tensile strength GRP ≤ 100 N
Cable weight 42 kg/km
Outer sheath, material PUR
Material conductor insulation Foamed PE
Conductor material Bare Cu litz wires
Insulation resistance ≥ 500 MΩ·km
Loop resistance ≤ 2...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VS-IP20/10G-IP20/10G-94F/5 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.