

INDUSTRIAL COMPONENT DATA

VS-PNRJ45-PNRJ45R-93K-0,3 1402511 PHOENIX CONTACT

Patch cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: VS-PNRJ45-PNRJ45R-93K-0,3



Manufacturer	PHOENIX CONTACT
MPN / Reference	VS-PNRJ45-PNRJ45R-93K-0,3
Catalog number	1402511
Category	Patch cord copper (twisted pair)
Minimum order	1 Pcs
Document ID	EO-0C68C66D6F
Generated	2026-08-04

Product Overview

Patch cable

Sercos III patch cable, shielded, star quadage, flexible AWG 22 (7 wires), RAL 3020 (traffic red), RJ45/IP20 male connector, straight, to RJ45/IP20 male, angled, length: 0.3 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data

Orderkey 1402511

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 321 (PC-2011)

GTIN 4046356622509

Weight per Piece (excluding packing) 46.620 g

Custom tariff number 85444210

Country of origin PL (Poland)

Ambient conditions

Degree of protection IP20

General data

Number of positions 4

Degree of pollution 1
Rated voltage (III/3) 72 V (DC)
Characteristics head 1
Color black
Material (component) CuSn (Contact)
Ni/Au (Contact surface)
PA (Contact carriers)
PA (Housing)
Insertion/withdrawal cycles ≥ 750
Ambient temperature (operation) -25 °C ... 80 °C
Characteristics head 2
Color black
Material (component) CuSn (Contact)
Ni/Au (Contact surface)
PA (Contact carriers)
PA (Housing)
Insertion/withdrawal cycles ≥ 750
Ambient temperature (operation) -25 °C ... 80 °C
Standards and Regulations
Flammability rating according to UL 94 V0
Cable
Cable type Sercos III
Cable type (abbreviation) 93K
UL AWM style 21694 (60°C / 600 V)
Signal type/category Sercos CAT5 (IEC 11801), 100 Mbps
Cable structure 1x4xAWG22/7; SF/TQ
Conductor cross section 4x 0.34 mm²
AWG signal line 22
Conductor structure signal line 7x 0.25 mm
Core diameter including insulation approx. 1.55 mm
Wire colors White, yellow, blue, orange
Type of pair shielding Aluminum-lined polyester foil
Overall twist Star quad
Shielding Tinned copper braided shield
External sheath, color signal red RAL 3020
Outer sheath thickness approx. 0.9 mm
External cable diameter D 6.5 mm ± 0.2 mm
Minimum bendin...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VS-PNRJ45-PNRJ45R-93K-0,3 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.