

## INDUSTRIAL COMPONENT DATA

# PC 16/ 3-ST-10,16 BD:L1-L3 1704741 PHOENIX CONTACT

## Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: PC 16/ 3-ST-10,16 BD:L1-L3



|                 |                            |
|-----------------|----------------------------|
| Manufacturer    | PHOENIX CONTACT            |
| MPN / Reference | PC 16/ 3-ST-10,16 BD:L1-L3 |
| Catalog number  | 1704741                    |
| Category        | Cable connector            |
| Minimum order   | 25 Pcs                     |
| Document ID     | EO-02DBE45624              |
| Generated       | 2026-08-04                 |

### Product Overview

Printed-circuit board connector

Connector for printed circuit board, nominal section: 16 mm<sup>2</sup>, color: green, nominal current: 76 A, nominal voltage (III/2): 1000 V, contact surface: silver, contact type: Female, number of potentials: 3, number of rows: 1, number of poles: 3, number of connections: 3, family of articles: PC 16/.. -ST, pitch: 10.16 mm, connection type: Screw connection with traction capsule, screw clamping form: L Longitudinal slot, conductor connection direction/printed circuit board: 0 °, clamping hook: - without clamping hook, plug-in system: COMBICON PC 16, locking: without, fixing type: without, packaging type: boxed

## STRUCTURED PRODUCT DATA

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

|              |                                        |
|--------------|----------------------------------------|
| Catalog path | PHOENIX CONTACT > PCB Connectors (PCC) |
|--------------|----------------------------------------|

### Additional Product Information

Key Commercial Data

Orderkey 1704741

Packing unit 50 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

GTIN 4017918995263

Weight per Piece (excluding packing) 26.740 g

Custom tariff number 85366990

Country of origin PL (Poland)

Dimensions

Length [ l ] 41.5 mm

Width [ w ] 30.32 mm

Height [ h ] 27.8 mm

Pitch 10.16 mm

Dimension a 20.32 mm

General

Range of articles PC 16/..-ST

Number of positions 3

Connection method Screw connection with tension sleeve

Rated voltage (III/3) 1000 V

Connection in acc. with standard EN-VDE

Nominal current I<sub>N</sub> 76 A

Nominal cross section 16 mm<sup>2</sup>

Connection data

Conductor cross section solid min. 0.75 mm<sup>2</sup>

Conductor cross section solid max. 16 mm<sup>2</sup>

Conductor cross section flexible min. 0.75 mm<sup>2</sup>

Conductor cross section flexible max. 16 mm<sup>2</sup>

Conductor cross section flexible, with ferrule without plastic sleeve min. 0.5 mm<sup>2</sup>

Conductor cross section flexible, with ferrule without plastic sleeve max. 16 mm<sup>2</sup>

Conductor cross section flexible, with ferrule with plastic sleeve min. 0.5 mm<sup>2</sup>

Conductor cross section flexible, with ferrule with plastic sleeve max. 10 mm<sup>2</sup>

Conductor cross section AWG min. 18

Conductor cross section AWG max. 6

2 conductors with same cross section, solid min. 0.75 mm<sup>2</sup>

2 conductors with same cross section, solid max. 6 mm<sup>2</sup>

2 conductors with same cross section, stranded min. 0.75 mm<sup>2</sup>

2 conductors with same cross section, stranded max. 6 mm<sup>2</sup>

2 conductors with same cross section, stranded, ferrules without plastic sleeve, min....

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PC 16/ 3-ST-10,16 BD:L1-L3 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.