

INDUSTRIAL COMPONENT DATA

PC 35 HC/ 5-GF-15,00 BK 1293270 PHOENIX CONTACT

Printed circuit board base case, nominal section: 35 mm², co..

Brand: PHOENIX CONTACT | Manufacturer Part Number: PC 35 HC/ 5-GF-15,00 BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	PC 35 HC/ 5-GF-15,00 BK
Catalog number	1293270
Category	Printed circuit board connector
Minimum order	10 Pcs
Document ID	EO-C4CC838B34
Generated	2026-08-05

Product Overview

Printed circuit board base case, nominal section: 35 mm², color: black, nominal current: 125 A, nominal voltage (III/2): 1000 V, contact surface: Ag, contact connection type: Male, number of rows: 1, number of poles: 5, family of articles: PC 35 HC/.. -GF, pitch: 15 mm, mounting: Wave soldering, pin arrangement: Linear pin arrangement, pin length [P]: 4.6 mm, number of solder pins per potential: 3, plug-in system: COMBICON PC 35, Plug-in face orientation: Standard, locking: Screw lock, clamping type: Air clamping (thread), packaging type: boxed

Base housing printed circuit board, nominal section: 35 mm², color: black, rated current: 125 A, dimensioning voltage (III/2): 1000 V, surface contacts: silver, contact type: Male, Number of rows: 1, Number of poles per row: 5, item family: PC 35 HC/.. -GF, pitch: 15 mm, mounting: Wave welding, pin arrangement: Linear pin arrangement, pin length [P]: 4.6 mm, plug-in system: POWER COMBICON 35, Plug-in face orientation: Standard, Locking: Screw lock, fixing type: Aerial fastening (thread), packaging type: boxed packaging: Standard, Locking: Screw locking: fixing

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

ETIM for 1293270 Connectors (EC002637)

Feature Name

Feature Value

Connector model (EF007495)

Fixed connector

Contact type (EF001587)

Pin
Number of plug-in contact rows (EF006935)
1
Modular spacing contacts (EF007326)
15 mm
Modular spacing connections (EF006827)
15 mm
Rated current I_n (EF008250)
125 A
Rated voltage (EF000228)
1000 V
Rated surge voltage (EF002993)
8 kV
Over voltage category (EF006785)
III
Pollution degree (EF006786)
2
Material of contact surface (EF004020)
Silver
Type of electric connection (EF003961)
Other
Diameter connection pin (EF006823)
3.6 mm
Length pin (EF006825)
4.6 mm
Material insulation body (EF007543)
Other
Housing colour (EF000136)
Black
Inflammability class of insulation material according to UL94 (EF002521)
V0
Operating temperature (EF002393)
-40 °C
Type of fastening (EF002442)
Other
Type of banding (EF007011)
Carton (for SMD)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PC 35 HC/ 5-GF-15,00 BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.