

INDUSTRIAL COMPONENT DATA

TVFKC 1,5/ 2-ST YE BD:38,37 SO 1706398 PHOENIX CONTACT Plug-in part, rated current: 10 A, number of poles: 2..

Brand: PHOENIX CONTACT | Manufacturer Part Number: TVFKC 1,5/ 2-ST YE BD:38,37 SO



Manufacturer	PHOENIX CONTACT
MPN / Reference	TVFKC 1,5/ 2-ST YE BD:38,37 SO
Catalog number	1706398
Category	Cable connector
Minimum order	2000 Pcs
Document ID	EO-106F30E654
Generated	2026-08-05

Product Overview

Plug-in part, rated current: 10 A, number of poles: 2, pitch: 5 mm, connection type: Push-in spring connection, color: yellow, contact surface: Tin

Connector for printed circuit board, nominal section: 1.5 mm², color: yellow, nominal current: 10 A, nominal voltage (III/2): 320 V, contact surface: Tin, contact type: Female, number of potentials: 2, number of rows: 1, number of poles: 2, number of connections: 4, family of articles: TVFKC 1.5/.. -ST, pitch: 5mm, connection type: Push-in spring connection, conductor/printed circuit board connection direction: 0°, clamping hook: - Clamping hook, plug-in system: COMBICON MSTB 2.5, locking: without, fixing type: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

Additional Product Information

Plug component, nominal current: 10 A, number of positions: 2, pitch: 5 mm, connection method: Push-in spring connection, color: yellow, contact surface: Tin

Key Commercial Data

Orderkey 1706398

Packing unit 1

GTIN 4046356860697

Custom tariff number 85366990

General

Range of articles TVFKC 1,5/..-ST

Type of contact Female connector

Number of positions 2

Connection method Push-in spring connection

Rated voltage (III/3) 250 V

Connection in acc. with standard EN-VDE

Nominal current IN 10 A

Nominal cross section 1.5 mm²**Connection data**Conductor cross section solid min. 0.2 mm²Conductor cross section solid max. 1.5 mm²Conductor cross section flexible min. 0.2 mm²Conductor cross section flexible max. 1.5 mm²Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²Conductor cross section flexible, with ferrule without plastic sleeve max. 1.5 mm²Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²Conductor cross section flexible, with ferrule with plastic sleeve max. 1.5 mm²

Conductor cross section AWG min. 24

Conductor cross section AWG max. 16

Standards and Regulations

Connection in acc. with standard EN-VDE

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

eCl@ss

eCl@ss 4.0 272607xx

eCl@ss 4.1 27260701

eCl@ss 5.0 27260701

eCl@ss 5.1 27141190

eCl@ss 6.0 27260704

eCl@ss 7.0 27440402

eCl@ss 8.0 27440309

eCl@ss 9.0 27440309

ETI...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / TVFKC 1,5/ 2-ST YE BD:38,37 SO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.