

INDUSTRIAL COMPONENT DATA

SAC-5P- 2,0-520/M12FR VA 1564655 PHOENIX CONTACT

Sensor/actuator cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-5P-2,0-520/M12FR VA



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-5P-2,0-520/M12FR VA
Catalog number	1564655
Category	Sensor-actuator patch cord
Minimum order	100 Pcs
Document ID	EO-49CFB261AD
Generated	2026-08-06

Product Overview

Sensor/actuator cable
Cable for sensors/actuators

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Key Commercial Data
Orderkey 1564655
Packing unit 5 pc
Minimum order quantity 50 pc
Note Made to Order (non-returnable)
GTIN 4046356308762
Weight per Piece (excluding packing) 127.980 g
Custom tariff number 85444290
Country of origin PL (Poland)
Dimensions
Length of cable 2 m
Ambient conditions
Degree of protection IP65
IP67

IP68

IP69K

General

Rated current at 40°C 4 A

Rated voltage 48 V AC

60 V DC

Number of positions 5

Coding A - standard

Status display No

Overvoltage category II

Degree of pollution 3

Insertion/withdrawal cycles ≥ 100

Material

Flammability rating according to UL 94 HB

Contact material CuSn

Contact surface material Ni/Au

Contact carrier material TPU GF

Material of grip body TPU, hardly inflammable, self-extinguishing

Material, knurls Stainless steel

Sealing material NBR

Standards and Regulations

Flammability rating according to UL 94 HB

Cable

Cable type PVC gray

Cable type (abbreviation) 520

Cable abbreviation LiYY

Conductor cross section 0.34 mm²

AWG signal line 22

Conductor structure signal line 42x 0.10 mm

Core diameter including insulation 1.45 mm ± 0.02 mm

Thickness, insulation ≥ 0.23 mm (Core insulation)

≥ 0.76 mm (Outer cable sheath)

Wire colors Brown, white, blue, black, gray

Overall twist 5 wires around filler to the core

Length of twist, overall twist 55 mm

External sheath, color gray RAL 7001

External cable diameter D 5.9 mm ± 0.15 mm

Cable weight 54 kg/km

Outer sheath, material PVC

Material, filler PVC

Material conductor insulation PVC

Conductor ma...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-5P-2,0-520/M12FR VA with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.