

INDUSTRIAL COMPONENT DATA

PC 4/ 8-STF-7,62 BK 1748804 PHOENIX CONTACT

Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: PC 4/ 8-STF-7,62 BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	PC 4/ 8-STF-7,62 BK
Catalog number	1748804
Category	Cable connector
Minimum order	50 Pcs
Document ID	EO-C30942DB6C
Generated	2026-08-03

Product Overview

Printed-circuit board connector

Connector for printed circuit board, nominal section: 4 mm², color: black, nominal current: 20 A, nominal voltage (III/2): 630 V, contact surface: Tin, contact type: Female, number of potentials: 8, number of rows: 1, number of poles: 8, number of connections: 8, family of articles: PC 4/.. -STF, pitch: 7.62 mm, connection type: Screw connection with traction capsule, screw clamping form: L Longitudinal slot, connection direction conductor/printed circuit board: 0 °, clamping hook: - Clamping hook, plug-in system: COMBICON PC 4, locking: Screw locking, fixing type: Air clamping (screw), packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data

Orderkey 1748804

Packing unit 50 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

GTIN 4046356309639

Weight per Piece (excluding packing) 35.720 g

Custom tariff number 85366990

Country of origin DE (Germany)

Dimensions

Length [l] 30.7 mm

Width [w] 76.18 mm

Height [h] 18.1 mm

Pitch 7.62 mm

Dimension a 53.34 mm

General

Range of articles PC 4/..-STF

Number of positions 8

Connection method Screw connection with tension sleeve

Rated voltage (III/3) 400 V

Connection in acc. with standard EN-VDE

Nominal current IN 20 A

Nominal cross section 4 mm²**Connection data**Conductor cross section solid min. 0.2 mm²Conductor cross section solid max. 4 mm²Conductor cross section flexible min. 0.2 mm²Conductor cross section flexible max. 4 mm²Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²Conductor cross section flexible, with ferrule without plastic sleeve max. 4 mm²Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²Conductor cross section flexible, with ferrule with plastic sleeve max. 4 mm²

Conductor cross section AWG min. 24

Conductor cross section AWG max. 10

2 conductors with same cross section, solid min. 0.2 mm²2 conductors with same cross section, solid max. 2.5 mm²2 conductors with same cross section, stranded min. 0.2 mm²2 conductors with same cross section, stranded max. 1.5 mm²

2 conductors with same cross section, stranded, ferrules without plastic sleeve, min. 0...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PC 4/ 8-STF-7,62 BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.