

INDUSTRIAL COMPONENT DATA

PC 5/10-ST2-7,62 1778023 PHOENIX CONTACT Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: PC 5/10-ST2-7,62



Manufacturer	PHOENIX CONTACT
MPN / Reference	PC 5/10-ST2-7,62
Catalog number	1778023
Category	Cable connector
Minimum order	50 Pcs
Document ID	EO-723855581
Generated	2026-08-05

Product Overview

Printed-circuit board connector

Connector for printed circuit board, nominal section: 6 mm², color: green, nominal current: 41 A, nominal voltage (III/2): 1000 V, contact surface: Tin, contact type: Female, number of potentials: 10, number of rows: 1, number of poles: 10, number of connections: 10, article family: PC 5/.. -ST2, pitch: 7.62 mm, connection type: Screw connection with traction capsule, screw clamping form: H1L Philipps-Recess with longitudinal groove, connection direction conductor/printed circuit board: 0 °, clamping hook: - without clamping hook, plug-in system: COMBICON PC 5, locking: without, fixing type: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

Additional Product Information

Key Commercial Data

Orderkey 1778023

Packing unit 50 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

GTIN 4046356523165

Weight per Piece (excluding packing) 43.960 g

Custom tariff number 85366990

Country of origin DE (Germany)

Dimensions

Length [l] 35.25 mm

Width [w] 76.2 mm

Height [h] 19.7 mm

Pitch 7.62 mm

Dimension a 68.58 mm

General

Range of articles PC 5/..-ST2

Number of positions 10

Connection method Screw connection with tension sleeve

Rated surge voltage (III/3) 8 kV

Rated surge voltage (III/2) 8 kV

Rated surge voltage (II/2) 6 kV

Rated voltage (III/3) 1000 V

Rated voltage (III/2) 1000 V

Rated voltage (II/2) 1000 V

Nominal current IN 41 A

Nominal cross section 6 mm²

Maximum load current 41 A

Insulating material PA

Flammability rating according to UL 94 V0

Internal cylindrical gage A4

Stripping length 10 mm

Screw thread M3

Tightening torque, min 0.5 Nm

Tightening torque max 0.8 Nm

Connection dataConductor cross section solid min. 0.2 mm²Conductor cross section solid max. 10 mm²Conductor cross section flexible min. 0.2 mm²Conductor cross section flexible max. 6 mm²Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²Conductor cross section flexible, with ferrule without plastic sleeve max. 6 mm²Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²Conductor cross section flexible, with ferrule with plastic sleeve max. 4 mm²

Conductor cross section AWG min. 24

Conductor cross sectio...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PC 5/10-ST2-7,62 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.