


INDUSTRIAL COMPONENT DATA

PC 5/ 2-G-7,62 P26 THT R44 1822024 PHOENIX CONTACT

Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: PC 5/ 2-G-7,62 P26 THT R44



Manufacturer	PHOENIX CONTACT
MPN / Reference	PC 5/ 2-G-7,62 P26 THT R44
Catalog number	1822024
Category	Printed circuit board connector
Minimum order	65 Pcs
Document ID	EO-BFE711F7E2
Generated	2026-08-06

Product Overview

Printed-circuit board connector

Printed circuit board base case, nominal section: 6 mm², color: black, nominal current: 41 A, nominal voltage (III/2): 630 V, contact surface: Tin, contact type: Male, number of rows: 1, number of poles: 2, family of articles: PC 5/..-G-THR, pitch: 7.62 mm, mounting: THR soldering/wave soldering, conductor connection direction/printed circuit board: 0 °, pin arrangement: Linear pin arrangement, pin length [P]: 2.6 mm, number of solder pins per potential: 3, plug-in system: COMBICON PC 5, Plug-in face orientation: Standard, lock: without, fixing type: without, packaging type: 44 mm wide strap, More user information and design recommendations on Through Hole Reflow technology can be found at: Downloads PCB headers, nominal cross section: 6 mm², color: black, nominal current: 41 A, rated voltage (III/2): 630 V, contact surface: Sn, contact connection type: Pin, number of rows: 1, number of positions: 2, product range: PC 5/..-G-THR, pitch: 7.62 mm, mounting: THR soldering / wave soldering, conductor/PCB connection direction: 0 °, pin layout: Linear pinning, solder pin [P]: 2.6 mm, number of solder pins per potential: 3, plug-in system: COMBICON PC 5, Pin connector pattern alignment: Standard, locking: without, mounting: without, type of packaging: 44 mm wide tape, For user information and design recommendations for through-hole reflow technology,....

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Technical dataProduct propertiesProduct type PCB headers

Product family PC 5/..-G-THR

Product line COMBICON Connectors L

Number of positions 2

Pitch 7.62 mm

Number of rows 1

Mounting flange without

Pin layout Linear pinning

Solder pins per potential 3

Data management status

Article revision 01

Electrical propertiesNominal current I_N 41 A

Nominal voltage U_N 630 V

Rated voltage (III/3) 500 V

Rated surge voltage (III/3) 6 kV

Rated voltage (III/2) 630 V

Rated surge voltage (III/2) 6 kV

Rated voltage (II/2) 800 V

Rated surge voltage (II/2) 6 kV

MountingMounting type THR soldering / wave soldering

Pin layout Linear pinning

Processing notes

Process Reflow/wave soldering

Moisture Sensitive Level MSL 3

Classification temperature T_c 245 °C

Solder cycles in the reflow 3

Material specificationsMaterial data - contact

Note WEEE/RoHS-compliant, free of whiskers according to IEC 60068-2-82/JEDEC JESD 201

Contact material Cu alloy

Surface characteristics hot-dip tin-plated

Metal surface contact area (top layer) Tin (4 - 8 μm Sn)

Metal surface soldering area (top layer) Tin (4 - 8 μm Sn)

Material data - housing

Color (Housing) black (9005)

Insulating material PA GF

Insulating material group IIIa

CTI according to IEC 60112 250

Flammability rating according to UL 94 V0

NotesNotes on operation In accordance with IEC 61984, COMBICON connectors have no switching power (COC). During designated use, they must not be plugged in or disconnected when carrying voltage or under load.

DimensionsDimension...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PC 5/ 2-G-7,62 P26 THT R44 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.