

INDUSTRIAL COMPONENT DATA

PC 5/ 3-G-7,62 P26 THT PA 1,3 1702216 PHOENIX CONTACT Header

Brand: PHOENIX CONTACT | Manufacturer Part Number: PC 5/ 3-G-7,62 P26 THT PA 1,3



Manufacturer	PHOENIX CONTACT
MPN / Reference	PC 5/ 3-G-7,62 P26 THT PA 1,3
Catalog number	1702216
Category	Printed circuit board connector
Minimum order	50 Pcs
Document ID	EO-2F51C4316A
Generated	2026-08-06

Product Overview

Header

Printed circuit board base case, nominal section: 6 mm², color: green, nominal current: 41 A, nominal voltage (III/2): 630 V, contact surface: Tin, contact type: Male, number of potentials: 2, number of rows: 1, number of poles: 3, number of connections: 2, family of items: PC 5/.. -G, pitch: 7.62 mm, mounting: THR soldering/wave soldering, conductor connection direction/printed circuit board: 0 °, pin arrangement: Linear pin arrangement, pin length [P]: 2.6 mm, number of solder pins per potential: 3, plug-in system: COMBICON PC 5, Plug-in face orientation: Standard, lock: without, fixing type: without, packaging type: boxed packaging

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data

Orderkey 1702216

Packing unit 1

GTIN 4046356575942

Custom tariff number 85366930

Dimensions

Length [L] 29.25 mm

Width 25.66 mm

Pitch 7.62 mm

Dimension a 15.24 mm

Width [w] 25.66 mm

Height [h] 16.89 mm

Height 14.29 mm

Length of the solder pin 2.6 mm

Length 29.25 mm

General

Range of articles PC 5/..-G

Rated voltage (III/3) 630 V

Connection in acc. with standard EN-VDE

Nominal current IN 41 A

Color green

Number of positions 3

Standards and Regulations

Connection in acc. with standard EN-VDE

CUL

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss

7.027440402eCl@ss 8.027440402eCl@ss 9.027440402

ETIM 3.0EC001121ETIM 4.0EC002637ETIM 5.0EC002637ETIM 6.0EC002637

UNSPSC 6.0130211810UNSPSC 7.090139121409UNSPSC 1139121409UNSPSC 12.0139121409UNSPSC

13.239121409

ETIM for 1702216 Connectors (EC002637)

Feature Name

Feature Value

Connector model (EF007495)

Fixed connector

Contact type (EF001587)

Pin

Number of poles (EF001391)

2

Number of plug-in contact rows (EF006935)

1

Modular spacing contacts (EF007326)

7.62 mm

Modular spacing connections (EF006827)

7.62 mm

Rated current In (EF008250)

41 A

Rated voltage (EF000228)

630 V

Rated surge voltage (EF002993)

6 kV

Over voltage category (EF006785)

III

Pollution degree (EF006786)

2

Material of contact surface (EF004020)...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PC 5/ 3-G-7,62 P26 THT PA 1,3 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.