


## INDUSTRIAL COMPONENT DATA

# PC 6-16/ 4-G-10,16 BK 1708378 PHOENIX CONTACT

## Feed-through header

Brand: PHOENIX CONTACT | Manufacturer Part Number: PC 6-16/ 4-G-10,16 BK



|                 |                                 |
|-----------------|---------------------------------|
| Manufacturer    | PHOENIX CONTACT                 |
| MPN / Reference | PC 6-16/ 4-G-10,16 BK           |
| Catalog number  | 1708378                         |
| Category        | Printed circuit board connector |
| Minimum order   | 1 Pcs                           |
| Document ID     | EO-A41C02EDF8                   |
| Generated       | 2026-08-05                      |

### Product Overview

PC 6-16/ 4-G-10,16 BK 1708378 PHOENIX CONTACT Feed-through header

## STRUCTURED PRODUCT DATA

### Technical Specifications

| TECHNICAL ATTRIBUTE                       | VALUE           |
|-------------------------------------------|-----------------|
| Connector model (EF007495)                | Fixed connector |
| Contact type (EF001587)                   | Pin             |
| Number of poles (EF001391)                | 4               |
| Number of plug-in contact rows (EF006935) | 1               |
| Modular spacing contacts (EF007326)       | 10.16 mm        |
| Modular spacing connections (EF006827)    | 10.16 mm        |
| Rated current I <sub>n</sub> (EF008250)   | 76 A            |
| Rated voltage (EF000228)                  | 1000 V          |
| Rated surge voltage (EF002993)            | 8 kV            |
| Over voltage category (EF006785)          | III             |
| Pollution degree (EF006786)               | 2               |
| Material of contact surface (EF004020)    | Silver          |
| Type of electric connection (EF003961)    | Other           |
| Diameter connection pin (EF006823)        | 1.7 mm          |
| Length pin (EF006825)                     | 5 mm            |

**CONTINUED****Technical Specifications**

| TECHNICAL ATTRIBUTE                                                      | VALUE            |
|--------------------------------------------------------------------------|------------------|
| Material insulation body (EF007543)                                      | Other            |
| Housing colour (EF000136)                                                | Black            |
| Inflammability class of insulation material according to UL94 (EF002521) | V0               |
| Operating temperature (EF002393)                                         | -40 °C           |
| Type of fastening (EF002442)                                             | Other            |
| Type of banding (EF007011)                                               | Carton (for SMD) |

**Classification & Catalog Path**

|              |                                        |
|--------------|----------------------------------------|
| eCl@ss 7.1   | 21043711                               |
| eCl@ss 8.0   | 21043711                               |
| eCl@ss 9.0   | 21043711                               |
| ETIM 5.0     | EC002246                               |
| ETIM 6.0     | EC002246                               |
| ETIM 7.0     | EC002246                               |
| Catalog path | PHOENIX CONTACT > PCB Connectors (PCC) |

**Additional Product Information****Feed-through header**

Base housing printed circuit board, nominal section: 6 mm<sup>2</sup>, color: black, rated current: 76 A (41 A in combination with PC 6 connector), sizing voltage (III/2): 1000 V, surface contacts: silver, contact type: Male, Number of potentials: 4, Number of rows: 1, Number of poles per row: 4, number of connections: 4, Item family: PC 6-16/.. -G, pitch: 10.16 mm, mounting: Wave welding, pin arrangement: Triple linear pin arrangement, pin length [P]: 5 mm, Stecksystem: POWER COMBICON 16, Locking: sin, packing type: boxed packaging

**REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW**

Send PHOENIX CONTACT / PC 6-16/ 4-G-10,16 BK with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.