

INDUSTRIAL COMPONENT DATA

PC 6-16/ 5-G1-10,16 BD:PE-L3 1587694 PHOENIX CONTACT

Printed circuit board base housing, nominal section: 16..

Brand: PHOENIX CONTACT | Manufacturer Part Number: PC 6-16/ 5-G1-10,16 BD:PE-L3



Manufacturer	PHOENIX CONTACT
MPN / Reference	PC 6-16/ 5-G1-10,16 BD:PE-L3
Catalog number	1587694
Category	Printed circuit board connector
Minimum order	1000 Pcs
Document ID	EO-232880DD78
Generated	2026-08-05

Product Overview

Printed circuit board base housing, nominal section: 16 mm², color: green, nominal current: 76 A (41 A in combination with PC 6 connector), nominal voltage (III/2): 1000 V, contact surface: Ag, contact connection type: Male, number of rows: 1, number of poles: 5, article family: PC 6-16/.. -G1, pitch: 10.16 mm, mounting: Wave soldering, pin arrangement: Linear pin arrangement, pin length [P]: 4 mm, number of solder pins per potential: 3, plug-in system: COMBICON PC 16, Plug-in face orientation: Standard, locking: without, clamping type: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

ETIM for 1587694 Connectors (EC002637)

Feature Name

Feature Value

Connector model (EF007495)

Fixed connector

Contact type (EF001587)

Pin

Number of plug-in contact rows (EF006935)

1

Modular spacing contacts (EF007326)

10.16 mm

Modular spacing connections (EF006827)

10.16 mm

Rated current I_n (EF008250)

76 A

Rated voltage (EF000228)

1000 V

Rated surge voltage (EF002993)

8 kV

Over voltage category (EF006785)

III

Pollution degree (EF006786)

2

Material of contact surface (EF004020)

Silver

Type of electric connection (EF003961)

Other

Diameter connection pin (EF006823)

1.7 mm

Length pin (EF006825)

4 mm

Material insulation body (EF007543)

Other

Housing colour (EF000136)

Green

Inflammability class of insulation material according to UL94 (EF002521)

V0

Operating temperature (EF002393)

-40 °C

Type of fastening (EF002442)

Other

Type of banding (EF007011)

Carton (for SMD)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PC 6-16/ 5-G1-10,16 BD:PE-L3 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.