


INDUSTRIAL COMPONENT DATA

PC 6-16/ 6-G-10,16 BUGY 4CP 1739211 PHOENIX CONTACT Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: PC 6-16/ 6-G-10,16 BUGY 4CP



Manufacturer	PHOENIX CONTACT
MPN / Reference	PC 6-16/ 6-G-10,16 BUGY 4CP
Catalog number	1739211
Category	Printed circuit board connector
Minimum order	50 Pcs
Document ID	EO-C51A54913A
Generated	2026-08-03

Product Overview

Printed-circuit board connector

Printed circuit board base housing, nominal section: 6 mm², color: bluish gray, nominal current: 76 A (41 A in combination with PC 6 connector), nominal voltage (III/2): 1000 V, contact surface: silver, contact type: Male, number of potentials: 6, number of rows: 1, number of poles: 6, number of connections: 6, family of articles: PC 6-16/.. -G, pitch: 10.16 mm, mounting: Wave soldering, pin arrangement: Linear pin arrangement, pin length [P]: 4 mm, number of solder pins per potential: 3, plug-in system: COMBICON PC 16, Plug-in face orientation: Standard, locking: without, fixing type: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1739211

Packing unit 50 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

GTIN 4046356286473

Weight per Piece (excluding packing) 21.630 g

Custom tariff number 85366990

Country of origin PL (Poland)

Dimensions

Length [l] 32 mm

Width 64 mm

Pitch 10.16 mm

Dimension a 50.8 mm

Width [w] 64 mm

Height [h] 17.7 mm

Height 13.7 mm

Length of the solder pin 4 mm

Pin dimensions 1 x 1.2 mm

Length 32 mm

General

Range of articles PC 6-16/..-G

Insulating material group I

Rated surge voltage (III/3) 8 kV

Rated surge voltage (III/2) 8 kV

Rated surge voltage (II/2) 6 kV

Rated voltage (III/3) 630 V

Rated voltage (III/2) 1000 V

Rated voltage (II/2) 1000 V

Connection in acc. with standard EN-VDE

Nominal current IN 76 A (41 A in combination with PC 6 plug)

Maximum load current 76 A

Color blue grey

Number of positions 6

Standards and Regulations

Connection in acc. with standard EN-VDE

CUL**Environmental Product Compliance**

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

ClassificationseCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss
7.027440402eCl@ss 8.027440402eCl@ss 9.027440402

ETIM 3.0EC001121ETIM 4.0EC002643ETIM 5.0EC002637ETIM 6.0EC002637

UNSPSC 6.0130211810UNSPSC 7.090139121409UNSPSC 1139121409UNSPSC 12.0139121409UNSPSC
13.239121409

ETIM for 1739211 Connectors (EC002637)

Feature Name**Feature Value**

Connector model (EF007495)

Fixed...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PC 6-16/ 6-G-10,16 BUGY 4CP with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.