

INDUSTRIAL COMPONENT DATA

MSTBT 2,5/ 4-ST GY7035BD:33-36 1701832 PHOENIX CONTACT Plug

Brand: PHOENIX CONTACT | Manufacturer Part Number: MSTBT 2,5/ 4-ST GY7035BD:33-36



Manufacturer	PHOENIX CONTACT
MPN / Reference	MSTBT 2,5/ 4-ST GY7035BD:33-36
Catalog number	1701832
Category	Cable connector
Minimum order	1000 Pcs
Document ID	EO-C9BB209F30
Generated	2026-08-03

Product Overview

Plug

Connector for printed circuit board, nominal section: 2.5 mm², color: light gray, nominal current: 12 A, dimensioning voltage (III/2): 320 V, contact surface: Tin, contact type: Connection female, Number of potentials: 4, Number of rows: 1, Number of poles per row: 4, number of connections: 4, article family: MSTBT 2.5/.. -ST, pitch: 5 mm, connection type: Screw connection with traction capsule, conductor connection direction/printed circuit board: 0°, Stecksystm: CLASSIC COMBICON, Lock: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

Additional Product Information

Key Commercial Data

Orderkey 1701832

Packing unit 1

GTIN 4046356562539

Custom tariff number 85366990

Dimensions

Length [l] 18.1 mm

Width [w] 20 mm

Height [h] 15 mm

Pitch 5 mm

Dimension a 15 mm

General

Range of articles MSTBT 2,5/...-ST

Number of positions 4

Connection method Screw connection with tension sleeve

Rated voltage (III/3) 250 V

Connection in acc. with standard EN-VDE

Nominal current IN 12 A

Nominal cross section 2.5 mm²

Connection data

Conductor cross section solid min. 0.2 mm²

Conductor cross section solid max. 2.5 mm²

Conductor cross section flexible min. 0.2 mm²

Conductor cross section flexible max. 2.5 mm²

Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule without plastic sleeve max. 2.5 mm²

Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule with plastic sleeve max. 2.5 mm²

Conductor cross section AWG min. 24

Conductor cross section AWG max. 12

2 conductors with same cross section, solid min. 0.2 mm²

2 conductors with same cross section, solid max. 1 mm²

2 conductors with same cross section, stranded min. 0.2 mm²

2 conductors with same cross section, stranded max. 1.5 mm²

2 conductors with same cross section, stranded, ferrules without plastic sleeve, min. 0.25 mm²

2 conductors with same cross section, stranded, ferrules without plastic sleeve, max. 1 mm²

2 conductors with same cross section, stranded...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MSTBT 2,5/ 4-ST GY7035BD:33-36 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.