


INDUSTRIAL COMPONENT DATA

PC 6/ 4-G-7,62 BK 1097713 PHOENIX CONTACT Housing base printed circuit board, nominal current: 41 A, number ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: PC 6/ 4-G-7,62 BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	PC 6/ 4-G-7,62 BK
Catalog number	1097713
Category	Printed circuit board connector
Minimum order	50 Pcs
Document ID	EO-B744181D77
Generated	2026-08-03

Product Overview

Housing base printed circuit board, nominal current: 41 A, number of poles: 4, pitch: 7.62 mm, color: black, surface of contact: Tin, assembly: wave Soldering

Printed circuit board base case, nominal section: 6 mm², color: black, nominal current: 41 A, nominal voltage (III/2): 630 V, contact surface: Tin, contact type: Male, number of rows: 1, number of poles: 4, article family: PC 6/.. -G, pitch: 7.62 mm, mounting: Wave soldering, pin arrangement: Linear pin arrangement, pin length [P]: 2.6 mm, number of solder pins per potential: 3, plug-in system: COMBICON PC 6, Plug-in face orientation: Standard, lock: without, fixing type: without, packaging type: boxed

PCB base strip, Nominal cross-section: 6 mm², Colour: black, Rated current: 41 A, Rated voltage (III/2): 630 V, Contact surface: Sn, Contact type: Pin, Number of rows: 1, Number of poles: 4, Article family: PC 6/.. -G, Pitch: 7.62 mm, Mounting: Wave Soldering, Pin Layout: Linear Pinning, Pin Length [P]: 2.6 mm, Number of Solder Pins per Potential: 3, Plug-in System: COMBICON PC 6, Mating Face Alignment: Standard, Locking: None, Mounting Type: None, Packaging Type: Packed in a Box

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Technical dataItem propertiesProduct Type PCB Floor Strip

Product family 6/.. pcs -G

Product Line COMBICON Connectors L

Number of poles 4

Grid dimension 7.62 mm

Number of rows 1

1

Pin layout Linear Pinning

Number of solder pins per potential 3

Data maintenance status

Article revision 00

Electrical propertiesNominal current IN 41 A

Rated voltage UN 630 V

Contact resistance 0.5 mΩ

Rated voltage (III/3) 630 V

Rated Surge Voltage (III/3) 6 kV

Rated voltage (III/2) 630 V

Rated Surge Voltage (III/2) 6 kV

Rated voltage (II/2) 1000 V

Rated Surge Voltage (II/2) 6 kV

AssemblyMounting type Wave Soldering

Pin layout Linear Pinning

Material specificationsMaterial information - Contact

Note WEEE/RoHS compliant, whisker-free according to IEC 60068-2-82/JEDEC JESD 201

Material Contact Cu alloy

Surface finish Electroplated

Metal Surface Contact Area (Top Layer) Tin (2 - 4 μm Sn)

Metal Surface Contact Area (Interlayer) Nickel (1.3 - 3 μm Ni)

Metal Surface Soldering Area (Top Layer) Tin (2 - 4 μm Sn)

Metal Surface Soldering Area (Interlayer) Nickel (1.3 - 3 μm Ni)

Material specifications - Housing

Color (Housing) black (9005)

Insulating material PA GF

Insulating material group I

CTI according to IEC 60112 600

Flammability class according to UL 94 V0

RemarksNote on operation COMBICON connectors are connectors without switching capacity (COC) in accordance with DIN EN 61984. When used as intended, they must not be plugged in or disconnected in a live or under load.

DimensionsDimensional drawing....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PC 6/ 4-G-7,62 BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.